NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

State Well No.

-10		 #	
12	حیا	 20	M

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON (Please type or print) G-366(

State Permit No.

(1) OWNER:	(11) WELL TESTS; Drawdown is amount lowered below static le	water level is	<i>(</i>
Name Myoue & James Black	Was a pump test made? Yes ☐ No If yes, by whom	A MADUV	and
Address All Dal 263	Yield: 200 gal./min. with 44 ft. drawdov	wn after	hrs.
Dervais Origin	"310 " 70 "	3 /.	3/5
(2) LÓCATION OF WELL:	" "		
17	Bailer test gal./min. with ft. drawd	own after	hrs.
County / WWON Driller's well number	Artesian flow g.p.m. Date		
34 Section 9420 T. S. R. 2 W W.	Temperature of water 5 Was a chemical analysis	made? 🗌 Yes 🎜	No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below to	seino	-
	195	176	
	Depth drilled / ft. Depth of completed we		<u>ft.</u>
	Formation: Describe by color, character, size of materic show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each c	ıl and structure the material in	, and each
A company of the comp	stratum penetrated, with at least one entry for each c	hange of formo	ition.
	MATERIAL	FROM T	0
(3) TYPE OF WORK (check):	lop Soil	03	5
Well Deepening Reconditioning Abandon	BHOWN C/2'S	52	5
It abandonment, describe material and procedure in Item 12.	Brown Sard	26 30	5
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Blue Clay.	30 60	0
Rotary C Driven C	Grey Sand	60 7	<u> </u>
Cable D Jetted C	Blace Clay	70 %	3
Irrigation Test Well Other Dug Bored	Block Sand	95 10	5
(6) CASING INSTALLED: Threaded Welded	Sand & Cravel	105 11	
	Blue Clay	111 11	16
"Diam. fromft. toft. Gage	SOLNE + CTOVE	116 17	5
"Diam, fromft. Gage			
(7) PERFORATIONS: Perforated? Yes No			
Type of perforator used		*-	
Size of perforations in. by in.			
perforations fromft. toft.			-
96 perforations from 16 ft. to 134 ft.			
perforations fromft. toft.		<u> </u>	
perforations fromft. toft.		 	
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes No			
Manufacturer's Name			
Model No.			_ ,.
Diam Slot size Set from ft. to ft.	Work started Alfa & 19/06 Completed	91149	to a
Diam. Slot size Set from ft. to ft.	Work started / 19/06 Completed / Date well drilling machine moved off of well dille	200 1	96.7
(9) CONSTRUCTION:		2. 19	600
Juddle Clar	(13) PUMP:	•	
Well seal—Material used in seal	Manufacturer's Name		
Depth of sealft. Was a packer used?	Туре:	H.P	
Diameter of well bore to bottom of seal in.	Water Well Contractor's Certification:		
Were any loose strata cemented off? Yes No Depth	water went contractor's Certification:		
Was a drive shoe used? Yes □ No	This well was drilled under my jurisdiction	and this repor	rt is
Was well gravel packed? Yes No Size of gravel:	true to the best of my knowledge and belief.		
Gravel placed from	NAME DYYE!		
Did any strata contain unusable water? Yes No	(Yerson time or corporation) (Ty	pe or print)	. 17
Type of water? Lepth of strata	Address / DOXS / C	PRVdis	_Xx 6
Method of sealing strata off	Drilling Machine Operator's License No.	179	
(10) WATER LEVELS:	m. 2	- Soften	
160 as below leid grunders Date (166 819)	[Signed] / Man Jose D	Levrill	
Static level	Justice went contagger)	- <i>I</i>	//
Artesian pressure lbs. per guare inch Date	Contractor's License No. 100 Date	<i>[</i>	66
(USE ADDITIONAL SH	EETS IF NECESSARY)		