NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGONAL 15 1967 State Well No. ...

(Please type or print) TE ENGINES Permit No.

5/2w-20F

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

MARCE (9)

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name J. E. BORDEN	Was a pump test made ☐ Yes ☐ No If yes, by whom		
Address RT # I. BOX 24	Yield: 420 gal./min. with I30 ft. drawdov	vn after	[I/2 .rs.
GERVAIS, OREGON	" " "		
(2) LOCATION OF WELL:	<i>n n</i> ·		
County MARION Driller's well number 40	Bailer test gal./min. with ft. drawde	own after	hrs.
OO S O LINOR	Artesian flow g.p.m. Date		
34 34 Section 20 T. 3 R.2 WEST W.M. Bearing and distance from section or subdivision corner	Temperature of water 54 Was a chemical analysis	made? 🔲 🖰	Yes 🔏 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below co	asing	
	Depth drilled I40 ft. Depth of completed we	a TAO	£+
	Formation: Describe by color, character, size of materic show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each c	the mater	lai in each
			701111111111111
(2) TYPE OF WORK (-LL-).	MATERIAL	FROM	TO
(3) TYPE OF WORK (check):	TOP SOIL		4
Well Deepening Reconditioning Abandon	BROWN CLAY	4	25
If abandonment, describe material and procedure in Item 12.	BROWN SILKY SAND	25	30-
(4) PROPOSED USE (check): (5) TYPE OF WELL:	BLUE CLAY	30	-55
Potenty II Dideon II	GREY SAND	55	6 5
Domestic industrial Municipal Coble	BLUE CLEY	65	-80
Irrigation X Test Well □ Other □ Dug □ Bored □	BLACK SAND	1 1	
(6) CASING INSTALLED: Threaded □ Welded □	BLUE CLAY	80	93
		93	103
	BLACK SANDO	103	115
"Diam. fromft. toft. Gage	BLUE CLAY	115	123 B
" Diam. from ft. to ft. Gage	GRAVEL	I23	140 t.
(7) PERFORATIONS: Perforated? XYes \(\square\) No			
Type of perforator used			
Principle - Princi	, and the second		-
Size of perforations 31/2 in. by 3/8 in. 276 perforations from 124 ft. to 138 ft.		1	
perforations from ft. to ft.			
perforations fromft. toft.		 	
perforations from ft. to ft.		1	
24:		+	
perforations from ft. to ft.		+	
(8) SCREENS: Well screen installed? ☐ Yes 🏗 No			<u> </u>
Manufacturer's Name		 	<u> </u>
Model No.		اـــــــــــــــــــــــــــــــــــــ	
Diam. Slot size Set from ft. to ft.	Work started MAY2 19 67 Completed M.	AY I2	19 67
Diam, Slot size Set from ft. to ft.	Date well drilling machine moved off of well and		
(9) CONSTRUCTION:	The state of the s	, 	19 67
	(13) PUMP:		
Well seal—Material used in seal PUDDLE CLAY	Manufacturer's Name	***************************************	
Depth of sealft. Wes a packer used?no	Type:	н.р	_
Diameter of well bore to bottom of seal in.	****		
Were any loose strata cemented off? [] Yes [No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? Yes □ No	This well was drilled under my jurisdiction	and this	report is
Was well gravel packed? Yes No Size of gravel:	true to the best of my knowledge and belief.		report in
Gravel placed fromft_ toft_	NIABER J. P. WEDDET!		
Did any strata contain unusable water? 🗌 Yes 🔼 No	NAME J.F. TERRELL (Person, firm or corporation) (Ty	pe or print)
	Address RT # I. BOX 57, GERVAIS, OR		
Towns 1/2.	A.A. A.		***************************************
Method of sealing strata off	Drilling Machine Operator's License No. 179	1	
(10) WATER LEVELS:	m. 200 Mal	1021	000)
Static level 15 ft. below land surface Date MAY 9.196	[Signed] (Water Well Contractor)	juv	
Artesian pressure lbg_per square inch Date	Comment of the same	12	67
	Contractor's License No. Date 1/104		, 192
USE ADDITIONAL SE	TRUBLES OF NIBERSHARV)		