NOTICE TO WATER WELL CONTRACTOR

The original and first copy WATER WELL REPORT of this report are to be filed with the

(Please type or print)
(Do not write above this line)

(Do not write above this line)

(Do not write above this line)

(Do not write above this line) STATE ENGINEER, SALEM, OREGON 97 within 30 days from the date of well completion. (10) LOCATION OF WELL: (1) OWNER:

Name Del Johnson	County Marion Driller's well no	umber	
Address 8000 9 E Roots	14 14 Section 22 T. 5S	R. OW W.M.	
Milwaukie, Oregon	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well 🖔 Deepening 🗌 Reconditioning 🗀 Abandon 🗀			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	roll	
(3) TYPE OF WELL: (4) PROPOSED USE (check):		. 9	
Rotary Driven Domestic K Industrial Municipal			
David Control	Static level 19 ft. below land s		
	Artesian pressure lbs. per squar	e inch. Date	
CASING INSTALLED: Threaded □ Welded ☑	(12) WELL LOG: Diameter of well h	<i>C</i> 11	
"Diam. from0 ft. to140 ft. Gage250	Diameter of Well k	pelow casing	
ft. Gage	Depth drilled 141 ft. Depth of compl		
ft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each stratur	and structure of materials;	
(A) DEDECDATIONS.	with at least one entry for each change of format	tion. Report each change in	
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal water-bearing strata.	
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	_Soil brown	0 2	
perforations from	Clay brown	2 8	
perforations from ft. to ft.	_ Clay sandy brown	8 27	
perforations from	Clay sandy blue	27 33	
(7) SCREENS: Well screen installed? Ves 5 No.	Clay blue	33 62	
West server Libraries L. 100 CA.110	Sand fine black	62 104 19	
Manufacturer's Name	Clay green	104 105	
TypeModel No DiamSlot sizeSet fromft. toft.	Sand with gravel black	105 108	
Diam. Slot size Set from ft. to ft.	1 1	108 117	
Set Holl It.	-Clay green	117 119	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	- Sand brown	119 133	
	Grav el black	 133 141 19 	
Was a pump test made? Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " "			
11 11			
Bailer test 40 gal./min. with 42 ft. drawdown after 1 hrs.			
Artesian flow g.p.m.			
Temperature of water 1 Depth artesian flow encountered ft.	Work started 5-37 19 74 Complete	3 :	
	Work started 5_3] 19 74 Complete Date well drilling machine moved off of well		
(9) CONSTRUCTION:		6-5 ¹⁹ 74	
Well seal—Material usedBentonite	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	direct supervision.	
Diameter of well bore to bottom of seal	best knowledge and belief.	above are true to my	
Diameter of well bore below seal	[Signed]	Date6-7, 1974	
Number of sacks of cement used in well sealsacks	(Drining Machine Operator)		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 527		
Brand name of bentonite <u>vellowstone</u>	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.			
	This well was drilled under my jurisdic true to the best of my knowledge and belie	ef.	
Was a drive shoe used? TXVes \(\subseteq \text{No Plugs} \)	Name A.C. Stites		
Did any strata contain unusable water? Yes X No	Name A.C. Stites 28290 5 Dryland Rd. Address	(Type or print)	
Type of water? depth of strata	Address	Oregon 97013	
Method of sealing strata off	[Signed]	OT CROTT ALOTA	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contrac	ctor)	
Gravel placed from ft. to ft.	Contractor's License No.533 Date6.	-7 19 7/	