NOTICE TO WATER WELL CONTRACTOR

WATER WELL REPORT 24 1967

The original and first copy of this report are to be filed with the	ELL REPORT 24 1967 F OREGON TO NO. 5	2w	-24
STATE ENGINEER, SALEM, OREGON 97310 STATE O within 30 days from the date of well completion. (Please ty	F OREGON pe or print) State Permit No		
(1) OWNER:	(11) WELL TESTS: Drawdown is amount	water lev	el is
Name RAY MATLOCK	Was a pump test made? Yes No If yes, by whom		ST.T.T
Address RT T BOX T73	Yield: 500 gal./min. with 34 Adrawdow		
GERVAIS, OREGON	" 400 " MS 22 "	n arter	30 "
(2) LOCATION OF WELL:	" " "		
	Bailer test gal./min. with ft. drawdo	www. often	hrs.
County MARTON Driller's well number 1213	Artesian flow g.p.m. Date	WII AILEI	1115.
34 34 Section 248 25. 5 S R. 2 W W.M.	Temperature of water Was a chemical analysis r	nada2 🗆	Ves C No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below ca		
	Depth drilled I50 ft. Depth of completed we	· ·	
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each cl	l and stru he mater lange of	icture, and ial in each formation.
	MATERIAL	FROM	TO
(3) TYPE OF WORK (check):	TOP SOIL	0	T
New Well Deepening Reconditioning Abandon	BROWN CLAY	Ĭ	Īo
bandonment, describe material and procedure in Item 12.	BROWN SANDY SILT	ĪO	35
(A) DDODOGED TIGE (-LL-). (5) WYDE OF THE T	GRAY SANDY SILT	35	80
(4) PROPOSED USE (check): (5) TYPE OF WELL:	BLACK SAND & GRAVEL	80	82
Domestic Industrial Municipal Rotary Driven Cable K Jetted	BLACK SAND	82	90
Irrigation Tast Well Other Dug Bored	GRAY CLAY & SAND	90	120
(6) CASING INSTALLED: Threaded Welded Welded W	BLACK SAND & GRAVEL	IZO	<u>I40</u>
Threaded Welded Welded Welded Top St. to Sop S	BLACK SAND & GRAVEL WITH WOOL		I50
ft. Gage ft. Gage			
ft. toft. Gage			
(7) PERFORATIONS: Perforated? X Yes No		-	
Type of perforator used MILLS		i	
Size of perforations 2 in. by 3/8 in.		 	
perforations from ft. to ft			<u>.</u>
		i i	
perforations from			
perforations from ft. to ft.			
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? Yes XNo	1 1:		

Manufacturer's Name			
Model No.			
m. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	Work started MAY 3 1967 Completed MA	12	1968
	Date well drilling machine moved off of well MAY	I5 I	9679
(9) CONSTRUCTION:	(13) PUMP:		
Well seal-Material used in seal CEMENT & PUDDLE CLAY	Manuscript and the second		
Depth of seal 20 ft. Was a packer used?	Manufacturer's Name		
Diameter of well bore to bottom of seal	Type: H.P.		
Were any loose strata cemented off? \(\text{Yes} \) No \(\text{Depth} \) Depth \(Water Well Contractor's Certification:		
Was a drive shoe used? MY Yes □ No	This well was drilled under my jurisdiction of		
Was well gravel packed? ☐ Yes II No Size of gravel:	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Gravel placed from ft. to ft.	NAME WILLAMETTE DRILLING CO		
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address RT. 2 BOX 276 SALEM, OREGON 97303		
Method of sealing strata off		_	
(10) WATER LEVELS:	Drilling Machine Operator's License No. 151		
Static level I8 ft. below land surface Date 5/I2/67	[Signed] 6 mul (V. Buer) (Water Well Contractor)		
Artesian pressure lbs. per square inch Date		'5 TO	2 17)
Artesian pressure ins. per square	Contractor's License No. 2 Date MAY 1	.O TA	2,719