NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPO

STATE OF OREGON

Male Well N

. 55/2W25

77 State Permit No.	
(Please type or print) JAN 7 7797 State Permit No.	
Do not write above this line R FESOURCE	

(1) OWNER:	(10) LOCATION OF WELL.		
Name Larry F. Scheidler	County Marion Driller's well number 1999		
Address 765 S. Pacific HWY Woodburn, OR 97071	1/4 1/4 Section 25 T. 5S	R. 2W	W.M.
	Bearing and distance from section or subdivision		
(2) TYPE OF WORK (check):			
New Well 🗶 Deepening 🗌 Reconditioning 🗀 Abandon 🗀			
If abandonment, describe material and procedure in Item 12.	(11) WATER I EVEL: Completed w		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.		
Potonic D Different PETE Land State Control of the	Depth at which water was first found 70 ft.		
Cable No Jetted Domestic Dindustrial Municipal Domestic	\Box Static level 29 ft. below land surface. Date $12/16/7$		
T g ☐ Bored ☐ Irrigation 🛣 Test Well ☐ Other ☐	Artesian pressure lbs. per squar	e inch. Date	
(5) CASING INSTALLED: Threaded Welded	(40) WITH T OC		
10 " Diam from top ft to 137 ft Gage 250	(12) WELL LOG: Diameter of well to	elow casing	*
"Diam. fromft, toft. Gage	Depth drilled 1/1/ it. Depth of completed well 1/3/ it.		
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size a		
DAMIN LAVIE MANAGEMENT OF THE STATE OF THE S	and show thickness and nature of each stratur with at least one entry for each change of format		•
PERFORATIONS: Perforated? T Yes \(\subseteq \) No.	position of Static Water Level and indicate prin		
Type of perforator used Millsknife	MATERIAL	From To	SWL
Size of perforations 7/16 in. by 2 3/4 in.	Topsoil	0 1	
200 perforations from 120 ft. to 136 ft.	Yellow Clay	1 30	
perforations from ft. to ft.	Blue Clay	30 70	
•	Black Sand		
perforations from ft. to ft.	Blue Clay	70 87 87 95	
(7) SCREENS: Well screen installed? Yes No	Black sand	1	
Manufacturer's Name	Black sand and gravel	1 1 1 1 1 1 1 1 1	
Type Model No	DIMON DUNING WHAT SERVET	115 137	
Diam. Slot size Set from ft. to ft.		<u> </u>	
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Tyes No If yes, by whom? driller			\vdash
700			
	a, t		
n			
" " "	TW-		
Bailer test gal./min. with ft. drawdown after hrs.			
Ariesian flow g.p.m.	Ŧ.		
apperature of water 53 Depth artesian flow encounteredft.	Work started 12/6/76 19 Complete	ed 12/1 6 /76	10
		12/16/76	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well		19
Well seal-Material used Portland cament	Drilling Machine Operator's Certification:		
Well sealed from land surface to 20 ft.	This well was constructed under my Materials used and information reported	direct super	vision.
Diameter of well bore to bottom of seal 14 in.	best knowledge and belief.	above are true	: to my
Diameter of well bore below sealin.	[Signed] Genald W. Moston (Ortilling Machine Operator)	Date 12 /17 /6	K 10
Number of sacks of cement used in well seal 12 sacks		2000 2004-24-440	J 10
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No	536	
Brand name of bentonite			
Number of pounds of bentonite per 100 galins	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? X Yes No Ples Size: location ft.	true to the best of my knowledge and beli	ei.	
Did any strata contain unusable water; Yes No	Name Willamette Drilling co. (Person, firm or corporation)	(Type or pri	nt)
Type of water? depth of strata	Address 1450 Barnick Rd. NB Sale	m. Orecon	ログスひつ
	Λ ./	wiwragnii	~à.4)U.)
Method of sealing strata off	[Signed] A allos Water Well Confer		
Was well gravel packed? Yes 700 Size of gravel:		•	
Gravel placed from ft.		/17/76	, 19
(USE ADDITIONAL SH	EETS IF NECESSARY)	SI	P*45656-119