NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

RECEIVED
NOV 18 1974
STATE ENGINEER
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 5S/2W-26
State Permit No.

2671
MARI

(1) OWNER:
Name Timofey Kalugin
Address Rt. 1 Box 5
Gervais, Oregon

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☒
8" Diam. from 0 ft. to 145 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used Mills Knife
Size of perforations 3/8 in. by 3 1/4 in.
105 perforations from 125 ft. to 135 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a ~~pump~~ air test made? ☒ Yes ☐ No If yes, by whom? Driller
Yield: 175 gal./min. with 50 ft. drawdown after 2 hrs.
" " "
" " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well 4 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☒ Yes ☐ No Plug Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Marion Driller's well number
¼ ¼ Section 26 T. 5S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 29 m. High school ft.
Static level 34 ft. below land surface. Date 10-31-74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing
Depth drilled 145 ft. Depth of completed well 145 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Top soil	0	2	
Clay brown	2	23	
Clay sand brown fine	23	29	
Sand black fine	29	30	
Clay blue	30	56	
Clay sand blue fine	56	70	
Sand black fine	70	83	
Clay blue	83	94	
Clay sand blue black fine	94	116	
Sand black fine	116	121	
Gravel med.	121	143	
Clay blue	143	145	

Work started 10-23-74 19 Completed 10-31 1974
Date well drilling machine moved off of well 10-31 1974

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] H. J. Wainwright Date 10-31, 1974
(Drilling Machine Operator)
Drilling Machine Operator's License No. 837

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name William D. Christenson Jr.
(Person, firm or corporation) (Type or print)
Address P.O. Box 343 Hubbard, Oregon
[Signed] William D. Christenson Jr.
(Water Well Contractor)
Contractor's License No. 511 Date 10-31, 1974

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119