

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED WATER WELL REPORT

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310

JUL 23 1979

STATE OF OREGON (Please type or print)

2700 MARI...

State Well No. 5s/2w-28 6b State Permit No. G-8167

WATER RESOURCES DEPT. (Do not write above this line)

(1) OWNER:

Name Wilbur Leutwyler Address 3965 Outfield Ct. Milwaukee, Oregon 97222

(2) TYPE OF WORK (check):

New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [ ] Driven [ ] Cable [X] Jetted [ ] Dug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [ ] Irrigation [X] Test Well [ ] Other [ ]

CASING INSTALLED:

10" Diam. from top ft. to 156 ft. Gage 250

PERFORATIONS:

Type of perforator used Mills Knife Perforator Size of perforations 7/16 in. by 2 3/4 in. 260 perforations from 133 ft. to 155 ft.

(7) SCREENS:

Well screen installed? [ ] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [X] Yes [ ] No If yes, by whom? driller Yield: 600 gal./min. with 20 ft. drawdown after 6 hrs.

(9) CONSTRUCTION:

Well seal—Material used Portland Cement Well sealed from land surface to 19 ft. Diameter of well bore to bottom of seal 14 in. Diameter of well bore below seal 10 in. Number of sacks of cement used in well seal 12 sacks How was cement grout placed? poured in from the top

(10) LOCATION OF WELL:

County Marion Driller's well number 2127 1/4 Section 28 T. 5S R. 2W W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 70 ft. Static level 10 ft. below land surface. Date 2/28/78 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing Depth drilled 156 ft. Depth of completed well 156 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Topsoil, Yellow Clay, Blue Clay, Black Sand, Black Sand Adn Gravel, Gray Clay, Black Sand And Gravel, Brown Sand and Gravel, Blue Clay.

Work started 2/11/78 19 Completed 2/28/78 19 Date well drilling machine moved off of well 2/28/78 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Donald W. Martin Date 2/28/78, 19 (Drilling Machine Operator)

Drilling Machine Operator's License No. 536

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Willamette Drilling Co. (Person, firm or corporation) (Type or print)

Address 1450 Barnick Rd. NE Salem, Or 97303

[Signed] Dallas P. Davis (Water Well Contractor)

Contractor's License No. 561 Date 2/28/78, 19