

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

2719
MARI:.....

WATER WELL REPORT

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE OF OREGON

(Please type or print)

(Do not write above this line)

WATER RESOURCES DEPT

State Well No. 5s/2W-29

State Permit No. _____

(1) OWNER:

Name Leo B. Stevens
Address 5844 Keene Rd. N.E.
Gervais, Oregon 97026

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Jetted
Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

10" Diam. from top ft. to 240 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used Mills Knife

Size of perforations 3/8 in. by 2 1/2 in.
310 perforations from 125 ft. to 140° ft.
140 perforations from 190 ft. to 198 ft.
330 perforations from 220 ft. to 238 ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name _____
Type _____ Model No. _____
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

a pump test made? Yes No If yes, by whom? driller
Yield: 600 gal./min. with 31 ft. drawdown after 2 1/2 hrs.
" " " " "
" " " " "
Peller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Portland Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 14 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal 10 1/2 sacks
How was cement grout placed? ~~mix~~ poured thru tremy pipe
Was a drive shoe used? Yes No Plugs _____ Size: location _____ ft.
Did any strata contain unusable water? Yes No
Type of water? _____ depth of strata _____
Method of sealing strata off _____
Was well gravel packed? Yes No Size of gravel: _____
Gravel placed from _____ ft. to _____ f

(10) LOCATION OF WELL:

County Marion Driller's well number 2288
1/4 1/4 Section 29 T. 5S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 67 ft.
Static level 15 ft. below land surface. Date 4/14/80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing _____
Depth drilled 240 ft. Depth of completed well 240 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Topsoil	0	1	
Yellow Clay	1	28	
Blue Clay	28	67	
Black Sand	67	105	
Sandy Blue Clay	105	119	
Brown Sand and Gravel	119	140	
Blue Clay	140	175	
Sandy Blue Clay	175	185	
Black Sand and Gravel	185	198	
Blue Clay	198	216	
Cemented Black Sand and Gravel	216	239	
Blue Clay	239	240	

Work started 2/14/80 19 Completed 4/14/80 19
Date well drilling machine moved off of well 4/15/80 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Ronald W. Minton Date 4/15/80, 19
(Drilling Machine Operator)

Drilling Machine Operator's License No. 536

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Willamette Drilling Co.
(Person, firm or corporation) (Type or print)

Address 7365 O'Neill Rd. N.E. Salem, Oregon 97303

[Signed] Dallas J. Davis
(Water Well Contractor)

Contractor's License No. 561 Date 4/15/80, 19

RETS IF NECESSARY