NOTICE TO WATER WELL CONTRACTOR EGE WEATER WELL REPORT of this report are to be filed with the AUG3 - 1972 STATE OF OREGON

STATE ENGINEER, SALEM, OFFICAL STATE ENGINEER'S type or print) within 30 days from the hate SALEM OFFICE (Do not write above this line)

State Well No. State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	
Name Irving Sears	County Marion Driller's well number 1655	
Address Rt. 1 Box 42 Gervais, Oregon		W.M.
	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well ☐ Deepening Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Retown D Driven D	Depth at which water was first found	<u>ft.</u>
Rotary	Static level 42 ft. below land surface. Date July	, 2 2,72
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date	
5) CASING INSTALLED: Threaded	(12) WELL LOG: Diameter of well below casing	ft.
ft, Gage	Formation: Describe color, texture, grain size and structure of mater	
	and show thickness and nature of each stratum and aquifer penetra	ated,
DEDECDATIONS.	with at least one entry for each change of formation. Report each change position of Static Water Level and indicate principal water-bearing st	
6) PERFORATIONS: Perforated? Yes \square No.		
Type of perforator used Mills Blade		WL
Size of perforations in. by in.	Black sand and gravel 97 100	
6 perforations from .at 100 ft. to ft.	Blue Clay, Sandy 100 124	
58perforations from124ft. to131ft.	Black sand and gravel 124 131	:
perforations fromft. toft.		
(7) COPENC.		
(7) SCREENS: Well screen installed? ☐ Yes ☑ No		
Manufacturer's Name	I	
Type Model No		
Diam. Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? 🗆 Yes 🏌 No 🗜 yes, by whom?	*	
Yield: gal./min. with ft. drawdown after hrs.		_
" " " "		
$n = \frac{1}{2} $		
Bailer test 40 gal./min. with 10 ft. drawdown after 1 hrs.		· · ·
		
Artesian flow g.p.m. Double extension flow encountered		
Emperature of water Depth artesian flow encountered ft.	1	972
(9) CONSTRUCTION:	Date well drilling machine moved off of well July 23, 1972	9
Well seal-Material used Cement and Puddle Clay	Drilling Machine Operator's Certification:	
Well sealed from land surface to18ft.	This well was constructed under my direct supervisi Materials used and information reported above are true to	ion.
Diameter of well bore to bottom of seal in.	best knowledge and belief.	my
Diameter of well bore below seal in.	and the same of th)
Number of sacks of cement used in well seal4sacks	(Drining Machine Operator)	
Number of sacks of bentonite used in well sal sacks	Drilling Machine Operator's License No141	**************************************
Brand name of bentonite	THE A. WHITE CO. L. C. L	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	*
of water lbs./100 gals.	This well was drilled under my jurisdiction and this repor true to the best of my knowledge and belief.	ct is
Was a drive shoe used? ☐ Yes ☐ No Pigs Size: location ft.	Name WILLAMETTE DRILLING COMPANY	
Did any strata contain unusable water? Tyes I No	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address .7641 35th Ave. NE Salem, Oregon 9730	0Z
Method of sealing strata off	1	
	[Signed] (Water Well Contractor)	
Was well gravel packed? [] Yes X No Size of gravel:		
Gravel placed fromft. ft.	Contractor's License No. 2 Date July 22, 1972, 19	J