MARI ...

NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

WELL REPORT

5/2w-29 J

of this report are to be filled with the STATE ENGINEER, SALEM, OREGON 97310 1 2 1967 STATE OF OREGON within 30 days from the date within 30 days from the date of the date of

State Permit No.

of well completion.	3-40-1-4 5		
(1) OWNER:	(11) WELL TESTS: Drawdown is amount of lowered below static le	vel	
Name ALAN HASLEBACKER	Was a pump test made? Wes So No If yes, by whom	13 23 mars mars a	
Address RT # I. BOX 494	Yield: gai./min. with it. drawdow	n after	JER'S
SALEM. OREGON	<u> </u>		<u>[/2                                    </u>
(2) LOCATION OF WELL:	<u>" 520 " 85 "</u>	I/	<u>/2 "</u>
MARTON	Bailer test gal./min. with ft. drawdo	wn after	hrs.
County Driffer's Well number	Artesian flow g.p.m. Date		
14 14 Section 29 T. 5 R. 2 WEST W.M.	Temperature of water 546Was a chemical analysis r	nade? 🔲	Yes 🔲 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below ca	sing	
	` '	-	
	Depth drilled II3 ft. Depth of completed we		
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each class	he mater	ial in each formation.
	MATERIAL	FROM	TO
(3) TYPE OF WORK (check):	TOP SOIL	0	2
We <b>X</b> □ Deepening □ Reconditioning □ Abandon □	BROWN CLAY	3	25
bandonment, describe material and procedure in Item 12.	BROWN STLKY SAND	25	27
(A) DRODOGED LIGE (A. A.). (E) MADE OF MELL.	BLUE CLAY	27	55
(4) PROPOSED USE (check): (5) TYPE OF WELL:	GRAY SAND	55	65
Domestic   Industrial   Municipal   Call	BEUR CLAY	65	80
Irrigation Test Well Other Dug Bored	BLACK SAND	80	87
(6) CASING INSTALLED: Threaded   Welded K	BLUE CLAY	87	95
I2	BEACK SAND	95	98
	SAND'& GRAVEL	98	TTZ
	DAILD & GRAVISH	30	++2
ft. toft. Gage		:	
(7) PERFORATIONS: Perforated? ★ Yes □ No			
Type of perforator used MILLS			1
Size of perforations 3/8 in. by 3 I/2 in.			
216 perforations from 100 ft. to 108 ft.			Win a
perforations from ft. to ft.			1
perforations from ft. to ft.		i	i
perforations from ft. to ft.		1	
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes 🛣 No			
Manufacturer's Name		<u> </u>	
Model No.			L
Slot size Set from ft. to ft.	Work started MAY TO 1967 Completed, TITN	13. ^	10/7
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well	<del>5-y</del> -	19 <b>67</b>
(9) CONSTRUCTION:	(13) PUMP:	10	1967
Well seal—Material used in seal .PUDDLE_CLAY	Manufacturer's Name		***************************************
Depth of seal	Type:	H.P	
Diameter of well bore to bottom of seal in.	Water Well Contractor's Certification:		
Were any loose strata cemented off? 🖸 Yes 🗶 No Depth			
Was a drive shoe used? ☐ No ==.	This well was drilled under my jurisdiction a	and this	report is
Was well gravel packed? ☐ Yes ∑ No Size of gravel:	true to the best of my knowledge and belief.		
Gravel placed from ft. to ft.	NAME (Person Tim or constitution) (Tv	***********	**********
Did any strata contain unusable water? 🔲 Yes 🕻 No	1	pe or print	t)
Type of water? depth of strata	Address RT # I, BOX 57, GERVAIS? O	REGON	•••••
Method of sealing strata off	Drilling Machine Operator's License No		
(10) WATER LEVELS:	m . J		)
TO MAYING 190	[Signed] / W. Jones Lee	rell	
Static level ft. below land surface Date 190	(Water Welf Contractor)		f ===
Artesian pressure lbs. per square inch Date	Contractor's License No. 460 Date JUNE 9		, <sub>19</sub> 27

(USE ADDITIONAL SHEETS IF NECESSARY)