

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

2735
MAR 1981

State Well No. 53-2w-30

State Permit No. G-9100

(1) OWNER:

Name Donald A. Nusom
Address 13501 River Rd. N.E.
Gervais, Oregon 97026

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Drivern
Jetted
Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
10" Diam. from top ft. to 157 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used Mills Knife
Size of perforations 3/8 in. by 2 1/2 in.
500 perforations from 110 ft. to 148 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

a pump test made? Yes No If yes, by whom? driller
Yield: 300 gal./min. with 18ft. drawdown after 1 1/2 hrs.
" 500 " " 35 " " 3 "
" " " " " " "
" " " " " " "
Artesian flow gal./min. with ft. drawdown after hrs.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Portland Cement & 5% Bentonite
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 15 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal 12 sacks
How was cement grout placed? pumped in thru conductor pipe
pipe
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number 2349
1/4 1/4 Section 30 T. 5S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 59 ft.
Static level 27 ft. below land surface. Date 1/8/81
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing

Depth drilled 157 ft. Depth of completed well 157 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Topsoil	0	1	
Yellow Clay	1	38	
Blue Clay	38	59	
Black Sand	59	75	
Blue Clay	75	93	
Black Sand	93	103	
Brown Sand and Gravel	103	150	
Blue Clay	150	157	

RECEIVED

JAN 19 1981

WATER RESOURCES DEPT
SALEM, OREGON

Work started 12/8/80 19 Completed 1/8/81 19
Date well drilling machine moved off of well 1/9/81 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Don Morton Date 1/9/81, 19...
(Drilling Machine Operator)

Drilling Machine Operator's License No. 536

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Willamette Drilling Co.
(Person, firm or corporation) (Type or print)

Address 7365 O'Neil Rd. N.E. Salem, Oregon 97303

[Signed] Dallas Davis
(Water Well Contractor)

Contractor's License No. 561 Date 1/9/81, 19...

(USE ADDITIONAL SHEETS IF NECESSARY)