

RECEIVED

MARI... 2772

NOTICE TO WATER WELL CONTRACTOR 11 1966

The original and first copy of this report are to be filed with the STATE ENGINEER

STATE ENGINEER

WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

OREGON STATE OF OREGON (Please type or print)

G-3588

State Well No. 5/2w-31A

State Permit No.

(1) OWNER:

Name Paul & Margaret Snyder
Address 2411 Bell 129
Blaine, Oregon

(2) LOCATION OF WELL:

County Marion Driller's well number 8
1/4 Section 31 T. 5 S. R. 2 W. W.M.
Bearing and distance from section or subdivision corner

(11) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes
Yield: 300 gal./min. with 11 ft. drawdown after 2 hrs.
450 " 22 " 2 "
500 " 22 " 2 "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water 54° Was a chemical analysis made? Yes

(12) WELL LOG:

Diameter of well below casing
Depth drilled 120 ft. Depth of completed well 120 ft.
Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

Table with columns: MATERIAL, FROM, TO. Entries include Top Soil, Brown Clay, Brown Sand, Blue Clay, Grey Sand, Black Sand, Blue Clay, Black Sand, Gravel Coarse - Water Bearing.

(3) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic Industrial Municipal Irrigation Test Well Other

(5) TYPE OF WELL:

Rotary Cable Dug Driven Jetted Bored

(6) CASING INSTALLED:

8" Diam. from 0 ft. to 120 ft. Gage 250
250" Diam. from 105 ft. to 118 ft.

(7) PERFORATIONS:

Perforated? Yes
Type of perforator used Mills
Size of perforations 3/8 in. by 3/4 in.
250 perforations from 105 ft. to 118 ft.

(8) SCREENS:

Well screen installed? No
Manufacturer's Name
Type Model No.
Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:

Well seal—Material used in seal Puddle Clay
Depth of seal 20 ft. Was a packer used? No
Diameter of well bore to bottom of seal 10 in.
Were any loose strata cemented off? No
Was a drive shoe used? Yes
Was well gravel packed? No Size of gravel:
Gravel placed from ft. to ft.
Did any strata contain unusable water? No
Type of water? depth of strata
Method of sealing strata off

(10) WATER LEVELS:

Static level 23 ft. below land surface Date July 7, 1966
Artesian pressure lbs. per square inch Date

Work started July 2 1966 Completed July 7 1966
Date well drilling machine moved off of well July 16 1966

(13) PUMP:

Manufacturer's Name
Type: H.P.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME J. F. Terrell (Person, firm or corporation) (Type or print)

Address Rt. 1, Box 57 Corvallis Ore

Drilling Machine Operator's License No. 179

[Signed] Mrs Joan B. Terrell (Water Well Contractor)

Contractor's License No. 460 Date, 19...