NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REI

STATE OF OREGON

(Please type or print)

State	Well No.	50/	1 2w	-3	2	ط
-------	----------	-----	---------	----	---	---

(Do not write above this line)

,		
State Permit	No.	

1) OWNER:	(10) LOCATION OF WELL:	
Mame Walter Gould	County Marion Driller's well nu	mber 79-6-C
ddress 4701 Concomly Rd. N.E.	14 NW 14 Section 32 T. 5S	R. 2W W.M.
Gervais, Oregon 97026	Bearing and distance from section or subdivision	n corner
2) TYPE OF WORK (check):		
New Well X Deepening □ Reconditioning □ Abandon □		
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.
3) TYPE OF WELL: (4) PROPOSED USE (check):	1 ` '	5 ft.
leters D Driven D	1	/ 10 0
Cable X Jetted D Domestic Industrial Municipal		
Dug Bored Irrigation K Test Well Other	Artesian pressure lbs. per square	inch. Date
CASING INSTALLED: Threaded Welded X 8 "Diam. from +1 ft. to 130 ft. Gage 250 ft. Gage ft. Gage	(12) WELL LOG: Diameter of well be Depth drilled 130 ft. Depth of complete	elow casing0
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each stratur with at least one entry for each change of format position of Static Water Level and indicate print	n and aquifer penetrated, ion. Report each change in
PERFORATIONS: Perforated? X Yes [No. Type of perforator used Torch	MATERIAL	From To SWL
Size of perforations 1 in. by 4 in.	Top Soil	0 2
80 perforations from 119 ft. to 129 ft.	Brewn Clav	2 14
perforations from ft. to ft.	Brown Sandy Clay	14 32
perforations from ft. to ft.	Gray Clay	32 37
	Gray Sandy Clay	37 85
(7) SCREENS: Well screen installed? Yes No	Black Sand	85 91 45
Manufacturer's Name	Black Sand & Fine Gravel	91 95
Type Model No	Black Sand & Med. Gravel	95 130 24
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft.		
Diam. Slot size Set from 11. to 11.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	DEGELVE	
Was a pump test made? Yes No If yes, by whom?	KEULIVE	U
	HH 7.01070	
Yield: gal./min. with ft. drawdown after hrs.	JUL 16 1979	
	WATER RESOURCES	DEPT
" 10 11 1	SALEM, OREGON	
Artesian flow g.p.m. perature of water 52 Depth artesian flow encountered ft.	Work started 6-18 1979 Complete	d 6-27 19 79
	Date well drilling machine moved off of well	6-28 19 79
(9) CONSTRUCTION:	Drilling Machine Operator's Certification:	
20	This well was constructed under my	direct supervision.
Well sealed from land surface to Diameter of well bore to bottom of seal12 in.	Materials used and information reported best knowledge and belief.	above are true to my
Diameter of well bore below seal in.		note 6-29070
Number of sacks of cement used in well seal 8 sacks	(Drilling Machine Operator)	
How was cement grout placed?	Drilling Machine Operator's License No	762
pressure grouted from bottom	Water Well Contractor's Certification:	
		-4:
	This well was drilled under my jurisditrue to the best of my knowledge and beli	
Was a drive shoe used? ★ Yes No Plugs Size: location ft.	Name Flores Well Drilling	9
Did any strata contain unusable water? ☐ Yes 💽 No	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address 12143 River Rd.N.E.	Gervais 97026
Method of sealing strata off	[Signed] Thomas O Flu	res
Was well gravel packed? Yes No Sie of gravel:	(Water Well Contra	actor)
Gravel placed from ft. to ft.	Contractor's License No590 Date	<u>6-29</u> , 19. 79