NOTICE TO WATER WELL CONTRACTOR

G-3826 G3281

5 196**3** 👶

5/2W-33HI

The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

WATER WELL REPORT AUG JUL 2 3 1903

STATE OF OREGON State Well No. . (Please type or print) State Permit No. **展學 於** 数

(1) OWNER: Oak Crest Farm	(11) WELL TESTS: Drawdown is amount of lowered below static lowered below static lowered by the property of t		is
Name Oak Crest Farm " Address 2770 Wallace Rd. NW	Yield: gal./min. with ft. drawdow		hrs.
Salem, Oregon	"		**
Datone Viveou	" "		"
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdov	vn after	hrs.
County Marion Driller's well number $5/2w-33$	Artesian flow g.p.m. Date		
14 14 Section T. R. W.M.	Temperature of water Was a chemical analysis	made? 🔲 Y	es_ 🗆 No
Bearing and distance from section or subdivision corner		A	
	(12) WELL LOG: Diameter of well below of		
	Depth drilled 214 ft. Depth of completed w		1
	Formation: Describe by color, character, size of materi show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each of	il and structured the materic change of f	cture, and all in each formation.
	MATERIAL	FROM	то
TYPE OF WORK (check):	Top soil	0	_ 1층_
w Well ☑ Deepening □ Reconditioning □ Abandon □	Clay, yellow	1분	1ĩ
If abandonment, describe material and procedure in Item 12.	Clay, silty yellow	11~	22
(1) PROPOSITO VICE (1 1) (F) HAVE OF WELL.	Clay, blue silty	22	63
(4) PROPOSED USE (check): (5) TYPE OF WELL:	_Clay,grey	63	68
Domestic Industrial Municipal Rotary Driven Cable Jetted	Sand, black	68	92
frrigation No Test Well Other Dug Bored	Clay, brown	92	114
(A) CACING INCOMITED. Worlded Cl. Wolded W	Gravel with clay	114	121
(6) CASING INSTALLED: Threaded ☐ Welded ☑ 145 ft. Gage •250	Clean sand & gravel	121	145
0 3/4 p. 1/10 st to 209 st case 250	Mucky black sand	145	165_
	Clean black sand	165	172_
"Diam. from ft. to ft. Gage ft. Gage	Sticky grey clay	172	181
(7) PERFORATIONS: Perforated? M Yes No	Black sand & wood	181	_196_
Type of perforator used Mills	Sand & gravel very sandy	196	209
Size of perforations 5/6 in. by 2 in.	Grey clay, sticky	209	21/1
450 perforations from 121½ ft. to 143½ ft.			
160 perforations from $198\frac{1}{2}$ ft. to 208 ft.		1	·
perforations from ft. to ft.		-	
perforations from ft. to ft.			
perforations from ft. to ft.			
(8) SCREENS: Well screen installed ☐ Yes ☐ No			
hufacturer's Name			
TypeModel No.			
Diam. Slot size Set from ft. to ft. to ft.	Work started 6/13 19 63 Completed 7/	/8/63	19
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well 7/8	1/2	19
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in sealBentonite	Manufacturer's Name		
Depth of seal	Type: H.P.		
Diameter of well bore to bottom of sealin.	17,000		
Were any loose strata cemented off? Tweet I No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? X Yes \(\Bar{\text{N}} \) No	This well was drilled under my jurisdiction	and this	report is
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	true to the best of my knowledge and belief.		
Gravel placed fromft. toft.	NAME Harry A Pohingon		
Did any strata contain unusable water? Ves No	NAME Harry A. Robinson (Person, firm or corporation) (Type or print)		
Type of water? Deuth of strata	Address 2214 Front St. NE Salem, Ore.		
Method of sealing strate off	Duilling Machine Occupation	•	
	Drilling Machine Operator's License No	}	
(10) WATER LEVELS: Static level 26 ft. below land surface Date 7/8/63	[Signed] / (Water Well Contractor)	een	
Static level	19 1 1 2 2 7	/19/63	4.0
Artesian pressure is lbs per square inch Bate	Contractor's License No Date		., 19