WATER WELL REPORT STATE OF OREGON



RECEIVED State Well No. 55 2w-34ad

NOV 2 2 1982

State Permit No.	
ot -	

WATE	RR	ESO	JRCE	s d	EPT.
:	SALE	EM, (REG	ON	

(1) OWNER:	(10) LOCATION OF WELL:		
Name O.M. Scott & Sons	County Warion Driller's well number		
Address 7644 Keene Rd. NE	SE 4 NE 4 Section 34 T. 5S R. 2W W.M.		
City ervais State Or.	Tax Lot # Lot Blk Subdivision		
(2) TYPE OF WORK (check):	Address at well location: Same as mailing		
New Well ☐ Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
	Depth at which water was first found 64 ft.		
	Static level 31 ft. below land surface. Date 2/20/8		
Rotary Air 🛱 Driven 🗆 Domestic 🔲 Industrial 🔲 Municipal 🗆 Bary Mud 🗆 Dug 🗆 Irrigation 🐪 Test Well 🗀 Other 🖂	Artesian pressure lbs. per square inch. Date		
Bored	(12) WELL LOG: Diameter of well below casing		
(5) CASING INSTALLED: Steel Plastic	Depth drilled 146 ft. Depth of completed well 144 ft.		
Threaded \square Welded \square	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry		
8 "Diam from +1 ft. to 115 ft. Gauge 250	for each change of formation. Report each change in position of Static Water Level		
"Diam. fromft. toft. Gauge	and indicate principal water-bearing strata.		
LINER INSTALLED: none	MATERIAL From To SWL		
	Soil med brn 0 2		
(6) PERFORATIONS: Perforated? □ Yes ∑ No	lay med brn 2 17		
Type of perforator used	Tlay sandy brn 17 31		
Size of perforations in, by in.	Clay med grey = 31 64		
perforations from	Sand fine blk 64 82		
perforations from ft. to ft.	lay sticky grey 82 99 rayel, sand, med grey 99 118		
perforations from ft. to ft.			
(7) SCREENS: Well screen installed? ☑ Yes ☐ No	Sand, blk some gravel 118 139 Cravel, loose course		
Manufacturer's Name Johnson	med-large, grev-brown 139 144		
8" telescope Stainless Model No 304	Clay sticky grey 144 146		
Diam. 72" Slot Size 15 Set from 123 ft. to 1.44 ft.			
Diam. Slot Size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
· · · · · · · · · · · · · · · · · · ·			
a pump test made? Yes No If yes, by whom?			
reld: gal./min. with ft. drawdown after hrs.			
200 51 5 71 - 112 4 1 1			
211. 0.1.1			
The state of the s			
tesian flow g.p.m. remperature of water Depth artesian flow encountered ft.	Work started 10/13 19 32 Completed 10/20 19 82		
Temperature of water	Work started 10/13 19 82 Completed 10/20 19 82 Date well drilling machine moved off of well 10/20 19 82		
(9) CONSTRUCTION: Special standards: Yes □ No □ Well seal_Material used Cement grout			
Well seal—Material used	Drilling Machine Operator's Certification: This well was Instructed under my Arect supervision. Materials used		
Diameter of well bore to bottom of seal in.	and information reported above the true my best knowledge and belief.		
Diameter of well bore below seal	[Signed] August Mar V.J. Date 10/21,982		
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator) Drilling Machine Operator's License No.		
How was cement grout placed? Press bumped	Diffing Machine Operator's Dicense No.		
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was pump installed?TypeHP Depthft.	Name West Coast Drilling Co. Inc.		
Was a drive shoe used? 🗵 Yes 🗆 No — Plugs Size: location ft. Did any strata contain unusable water? 📋 Yes 🖟 No	(Person, firm or corporation) (Type or print)		
	Address 220 Academy St. W. Angel. Or.		
	[Signed] Kalles & Stables		
Method of sealing strata off Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor) Contractor's License No. A Date 10/21 1982.		
Gravel placed from	Date		