## The original and first copy of this report are to be filed with the

2820 NARIState Well No.

State Permit No. .....

STATE ENGINEER, SALEM, OREGOSTATE ENGINEER, SALEM, ORGANIZATE ENGINEER, ORGANIZATE ENGINEER, ORGANIZATE ENGINEER, ORGANIZATE ENGINEER, ORGANIZ

(1) OWNER:	(11) LOCATION OF WELL:		
Name TIMOTHY STRUBHAR	County MRRON Driller's well number		
Address 8795 PORTLAND RD N.E. BROOKS ORE.	4 NW 4 Section 34 т. 55 R. 2 W. W.M.		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner		
New Well   Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):			
Rotary Driven Domestic Industrial Municipal Domestic	(12) WELL LOG: Diameter of well	below casing	10
Cable  Jetted    Domestic   Industrial  Municipal   Dug	Depth drilled 167' ft. Depth of compl	eted well	67' ft.
	Formation: Describe color, texture, grain size		
CASING INSTALLED: Threaded Welded Welded to the Gage Threaded Thre	and show thickness and nature of each stratu with at least one entry for each change of form		
•	in position of Static Water Level as drilling pro	oceeds. Note dr	illing rates.
" Diam. from ft. to ft. Gage	MATERIAL	From To	swL
" Diam, from ft. to ft. Gage	TOPSOIL	0 /	
PERFORATIONS: Perforated? Yes No.	CLAY YELLOW COLOR	/ 2	
Type of perforator used MILLS	CLAY BLUE - SILTY CLAY BLUE STICKY	2/5	<del>Z</del>
Size of perforations in. by 3; 722 in.	CLAY BLUE STICKY SAND-BLACK- FINE	59 6	
350 perforations from 1250 tt. to 15/2' tt.	CLAY GRAY - STICKY	90 10	
perforations fromft. toft.	CLAY STONE SOFT	100 11	20
perforations fromft. toft.	COMBLONERATE	100	25-18-11
perforations from ft. to ft.	GRAVEL & SAMO 1"- BR	TON 125-	30
perforations from ft. to ft.	GRAVEL 3'- BLUE		9 18'11"
(7) SCREENS: Well screen installed?   Yes You	CONGLORIERATE - YELLOW	139 14	ry .
Manufacturer's Name	CLAYSTONE FIRM.	144 15	٧
Type Model No.	SAHO BLUE - FINE	154 16	<b>3</b>
Diam. Slot size Set from ft. to ft.		<del>                                     </del>	
Diam. Slot size Set from ft. to ft.		<del> </del>	<del></del> _
(8) WATER LEVEL: Completed well.			
Static level /8'//" ft. below land surface Date 6-/-68			
(9) WELL TESTS: Drawdown is amount water level is lowered below static level	A1.		
Was a pump test made? 🗌 Yes 👗 No If yes, by whom?			
Vield: gal./min. with ft. drawdown after hrs.	Work started 6 4 - 1968 Complet		
,	Date well drilling machine moved off of well	6-11.	- 1968
" " "	Drilling Machine Operator's Certification:		
Bailer test 75 gal./min. with \$\forall ft drawdown after \infty hrs.	This well was constructed under my di	rect supervisi	on. Mate-
Artesian flow g.p.m. Date	rials used and information reported above knowledge and belief.	re are true to	my best
Temperature of water 57 Was a chemical analysis made?   Yes	[Signed] B. Jeeef	Date 6- //	- 10/8
Temperature of water 37 was a chemical analysis mader [] fes 5000	(Drilling Machine Operator)	Date Warming	., 19.9.
(10) CONSTRUCTION:	Drilling Machine Operator's License No	187.	
Well seal—Material used BPNTONITE	g	·	
Depth of seal 63'	Water Well Contractor's Certification:		
Diameter of well bore to bottom of seal in.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Were any loose strata cemented off? Tyes No Depth	NAME J. A. SHEEDA SO	ne S	
Was a drive shoe used? Yes No	(Person, firm or corporation)	(Type or prin	nt)
Did any strata contain unusable water? A yes \( \text{No} \)  Type of water? \( \sum_{\text{No}} \text{PO} \( \sum_{\text{O}} \text{V} \text{Q} \) depth of strata \( \text{65} \cdot \text{PO} \( \sum_{\text{O}} \text{V} \)	Address 3910 SILUGRION	en SAL.	ou Ons
Type of water? SANDY depth of strata 65 VO 90	De l	***************************************	
Method of sealing strata off (456),	[Signed]		******
Was well gravel packed? ☐ Yes ☑No Size of gravel:	(Water Well Contrac	tor)	,
Gravel placed from ft. to ft.	Contractor's License No Date	00 × (/-	, 19.
- (ITSE ADDITIONAL CH	DETE IN MEGRACIANTS		