

**RECEIVED**  
MAY 9 1957

**WATER WELL REPORT**  
STATE OF OREGON

State Well No. 5/2W-34D(1)  
State Permit No. G459

(1) OWNER: Willard F. Begin  
Name  
Address SALEM, OREGON  
Rt. 7 Gervais, Oregon

(2) LOCATION OF WELL:  
County Marion Owner's number, if any—  
NW 1/4 NW 1/4 Section 34 T. 5S R. 2W W.M.

Bearing and distance from section or subdivision corner  
Well is located S.300 ft. and S.74 deg.  
45 min. E.1120 ft. and S. 131 ft. and W.  
131 ft. from the N.W. corner of Section  
34, T.5 S., R.2 West of W.M. in Marion  
County, Oregon

(3) TYPE OF WORK (check):  
New Well  Deepening  Reconditioning  Abandon   
If abandonment, describe material and procedure in Item 11.

(4) PROPOSED USE (check):  
Domestic  Industrial  Municipal   
Irrigation  Test Well  Other

(5) TYPE OF WELL:  
Rotary  Driven   
Cable  Jetted   
Dug  Bored

(6) CASING INSTALLED: Threaded  Welded   
8" Diam. from top 133 ft. to 133 ft. Gage .277  
" Diam. from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Gage \_\_\_\_\_  
" Diam. from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Gage \_\_\_\_\_

(7) PERFORATIONS: Perforated?  Yes  No  
Type of perforator used MILLS  
SIZE of perforations 3/8 X 1/4 in. by \_\_\_\_\_ in.  
120 perforations from \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
124 perforations from \_\_\_\_\_ ft. to 133 ft.  
perforations from \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
perforations from \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
perforations from \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

(8) SCREENS: Well screen installed  Yes  No  
Manufacturer's Name \_\_\_\_\_  
Type \_\_\_\_\_ Model No. \_\_\_\_\_  
Diam. \_\_\_\_\_ Slot size \_\_\_\_\_ Set from \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
Diam. \_\_\_\_\_ Slot size \_\_\_\_\_ Set from \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

(9) CONSTRUCTION:  
Was well gravel packed?  Yes  No Size of gravel: \_\_\_\_\_  
Gravel placed from \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
Was a surface seal provided?  Yes  No To what depth? 20 ft.  
Material used in seal— puddled clay  
Did any strata contain unusable water?  Yes  No  
Type of water? \_\_\_\_\_ Depth of strata \_\_\_\_\_  
Method of sealing strata off \_\_\_\_\_

(10) WATER LEVELS:  
Static level 13 ft. below land surface Date 3-20-57  
Artesian pressure \_\_\_\_\_ lbs. per square inch Date \_\_\_\_\_

Log Accepted by Willard F. Begin  
[Signed] \_\_\_\_\_ Date 3-20-57  
(Owner)

(11) WELL TESTS: Drawdown is amount water level is lowered below static level  
Was a pump test made?  Yes  No If yes, by whom?  
Yield: 400 gal./min. with 48 ft. drawdown after 4 hrs.  
\*\*\*Note\*\*\* " " " "  
" Pump test below " " "  
Bailer test gal./min. with \_\_\_\_\_ ft. drawdown after \_\_\_\_\_ hrs.  
Artesian flow \_\_\_\_\_ g.p.m. Date \_\_\_\_\_  
Temperature of water 56 Was a chemical analysis made?  Yes  No

(12) WELL LOG: Diameter of well 8 inches.  
Depth drilled 133 ft. Depth of completed well 133 ft.  
Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

MATERIAL	FROM	TO
Top Soil	0	2
yellow clay	2	26
Blue clay	26	72
Black Sand (Water)	72	93
Brown clay	93	117
Brown sand and some S. Gravel	117	121
Black sand & Gravel (Water)	121	133

\*\*\*Pump Test\*\*\*

400 G.P.M.	@	61 ft.
350 "	@	54
300 "	@	46
250 "	@	42
200 "	@	38
150 "	@	31

After 4 hrs. Pumping

Work started 2-27-57 19 \_\_\_\_\_ Completed 3-20-57 19 \_\_\_\_\_

(13) PUMP:  
Manufacturer's Name \_\_\_\_\_  
Type: \_\_\_\_\_ H.P. \_\_\_\_\_

Well Driller's Statement:  
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.  
NAME Orville Wymore  
(Person, firm, or corporation) (Type or print)  
Address Box 101 Brooks, Oregon  
Driller's well number 325  
[Signed] Orville Wymore  
(Well Driller)  
License No. 88 Date Mar. 20, 1957 19 \_\_\_\_\_