NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with th

Type of water?

Gravel placed from

Method of sealing strata off

Was well gravel packed?
Yes To

Did any strata contain unusable water? [] Yes 🗶 No

Size of gravel:

STATE ENGINEER, SALEM, ORECAN 97310 R 3 0 1971 (Please type within 30 days from the date) Property of the date of	e or print)	0	db		
	bove this line)				
STATE ENGIN					
(1) OWNER:	(10) LOCATION OF WELL:				
• • • • • • • • • • • • • • • • • • • •	County Marion Driller's well no	ımber 1541			
Name William Albright Address Rt. 1 Box 7 Gervais, Oregon	SE 14 NW 14 Section 37-34 T. 58	R. 2W	W.M.		
Address Rt. 1 Box / Gelvals, Oregon	Bearing and distance from section or subdivisi				
(2) TYPE OF WORK (check):	Dearing and and	1 4 2			
New Well Deepening □ Reconditioning □ Abandon □			1 1		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	zell.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	72	ft.		
Rotary Driven Domestic Industrial Municipal		surface. Dat	26-71		
Cable Jetted Dug Bored Irrigation Test Well Other		re inch. Date			
GACTAG TAGMALLED.	(10) YUNY T OC				
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well	below casing			
12 " Diam. from top ft. to 246 ft. Gage 250	Depth drilled 246 ft. Depth of comp		46 ft.		
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	and structure of	materials;		
"Diam, from ft. toft. Gage	with at least one entry for each change of forma	ition. Report each	h change in		
PERFORATIONS: Perforated? \(\mathbb{X} \text{Yes} \text{INo.} \)	position of Static Water Level and indicate prin	icipal water-bear	ring strata.		
Type of perforator used Mills	MATERIAL	From To	SWL		
1 to be 21 in	Top Soil	0 2			
Size of perforations 7 m. by 23 m. 360 perforations from 123 ft. to 145 ft.	Yellow Clay	2 30			
312 perforations from 223 ft. to 245 ft.	Blue clay	30 72			
perforations fromft. toft		72 95			
	Blue clay	95 120			
(7) SCREENS: Well screen installed? ☐ Yes ▼No	<u>Gravel</u>	120 145			
Manufacturer's Name	Blue Clay	145 223			
Type	Gravel	223 246			
Diam. Slot size Set from ft. to ft.					
Diam. Slot size Set from ft. to ft.					
(8) WELL TESTS: Drawdown is amount water level is lowered below static level					
Was a pump test made? Yes \(\bar{Y}\) No If yes, by whom? Driller					
Vield: 400 gal/min, with 21 ft. drawdown after 6 hrs					
500 " 25 " 6 "		 	-		
" 600 " 33 " 6 "	* -				
20		+			
The state of the s					
Artesian flow g.p.m.					
perature of water Depth artestan flow encountered fr	- \	-	•		
(9) CONSTRUCTION:	Date well drilling machine moved off of well		971 19		
Well seal-Material used Cement and Puddle Clay	Drilling Machine Operator's Certification		onwicion		
Well cooled from land surface to	This well was constructed under m. Materials used and information reported	y direct sup d above are to	rue to my		
Diameter of well bore to bottom of seal in.	best knowledge and belief.				
Dismeter of well hore below seal in.	[Signed] Grilling Machine Operator)				
Number of sacks of cement used in well seal sack	brilling Machine Operator's License No.	536			
Number of sacks of bentonite used in well seal sack	s Diffing machine operators become 100				
Brand name of bentonite	Water Well Contractor's Certification:	£			
Number of pounds of bentonite per 100 galons	This well was drilled under my juris	diction and thi	s report is		
of waterlbs,/100 gal	true to the best of my knowledge and b	eli ef .	=		
Was a drive shoe used? XYes \(\subseteq \text{No Plugs} \) Size: location fi	Name WILLAMETTE DRILLING COME	ANY			

Name WILLAMETTE DRILLING COMPANY (Person, firm or corporation)

(Type or print)

Address	7641	.35th	Ave.	.NE	Salem.	.Oregon.	9.73.03
		:		_ · /~	. ,		
[Signed]	Pin	il.	10.5	S	ica		
[pr8rrè#]		Marie and The Control of the Control	(W	ater We	ell Contracto	r)	

Contractor's License No. 2 Date 4-29-71 , 19