NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be

filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT EIVEU

STATE OF OREGONOV 1 8 1974

(Please type or print) ATE ENGINEER

State Well No	55/2w-35
---------------	----------

(Do not write above this line) OREGOIL

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	mher	
Name Timofey Kalugin	County Marion Driller's well nu	0	W.M.
Address Rt. 1 Bex 5	/4	16.	- VV .IVI.
Gervais, Oregon	Searing and distance from section or subdivisio	n corner	
(2) TYPE OF WORK (check):	The second secon		
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.	
7 1	Depth at which water was first found	2	ft.
(3) 1111 01 1122	Static level 32 ft. below land s	urface. Date	10-22-7
Domestic Dimestra	Diade level		
Cable	Artesian pressure lbs. per squar		
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well by	oelow casing	
CASING INSTALLED. Introduced 1 Gage 250	Depth drilled 140 ft. Depth of compl		140 ft.
	Formation: Describe color, texture, grain size a		materials;
" Diam. from			
" Diam. from ft. to ft. Gage	with at least one entry for each change of formar position of Static Water Level and indicate prin	THUIL TENDITO CACI	e crowing a are
PERFORATIONS: Perforated? T Yes No.	position of Static Water Level and indicate print		SWL
Type of perforator used Mills Knife	MATERIAL	From To	SWL
3/8 in hy 34 in.	Tep soil	0 2	
Size of perforations 3/0 in. by 34 in. 100 perforations from 124 ft. to 132 ft.	Clay brown	2 20	
100 perforations from	Clay sand brown fine	20 27	 -
perforations fromft. toft. perforations fromft. toft.	Clay blue	27 39	
perforations from	Clay sand blue black fine	39 62	
(7) SCREENS: Well screen installed? Yes No	Sand black fine	62 76	
Manufacturer's Name	Clay blue	76 94 91 111	
Type Model No.	Clay sand blue black fine		18
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	Sand black fine	118 13	
Diam Slot size Set from ft. to ft.	Clay brown	137 140	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Oldy biolist		
Was a pulliftest made? Yes No If yes, by whom? Driller			
Yield: 150 gal./min. with 50 ft. drawdown after 2 hrs.	a second		
" "			
n n			
Bailer test gal./min. with ft. drawdown after hrs.			
1964年 1965年	The second secon		
The state of the s	Work started 10-15 19 74 Comple	eted 1	0-2219 7l
perature of water Depth artesian flow encountered	Date well drilling machine moved off of well		0-2219 71
(9) CONSTRUCTION:			
Well seal—Material usedCement	Drilling Machine Operator's Certification This well was constructed under m	w direct sur	ervision.
Well sealed from land surface to	Materials used and information reported	d above are f	rue to my
Diameter of well bore to bottom of seal 12 in.	best knowledge and belief.		
in.	[Signed (Drilling Machine Operator)	Date10-	, 1 7
Number of casks of cement used in well seal sacks	Drilling Machine Operator's License No	837	7
Number of sacks of bentonite used in well sealsacks			
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my juris	sdiction and th	is report is
Ibs./100 gais.	true to the best of my knowledge and b	pener.	
Was a drive shoe used? Yes ☐ No Plugs Size: location ft.	Name WILLIAM D. CAPTS CENSOR (Person, firm or corporation)	(Type or	r print)
Did any strata contain unusable water? Yes Wo	Address P. W. Bern 313 Advisoria,	Øregon	.
Type of water? depth of strata	1/1/1/	1/2	7
Method of sealing strata off	[Signed] (Water Well Co	wtractor)	.
Was well gravel packed? Yes No Size of gravel:	511	10-31	1 1974
Gravel placed fromft. toft.	Contractor's License No Date		SP*45656-11
	THE PARTY OF THE P		SP#45656-11