

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

RECEIVED

WATER WELL REPORT

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE OF OREGON
(Please type or print)

JAN 4 1979

WATER RESOURCES DEPT.

(Do not write above this line)

MAR 28 1979
85/2w-35
off. G-9131
Customer says it is a domestic well - not irrigation Co 29-79

(1) OWNER: SALEM, OREGON

Name Wayra Farms
Address 915 Marion St.
Woodburn, Oregon 97071

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):
Rotary Driven Domestic Industrial Municipal
Cable Jetted Irrigation Test Well Other
Dug Bored

CASING INSTALLED: Threaded Welded
8" Diam. from top ft. to 144 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? Yes No.
Type of perforator used Mills Knife
Size of perforations 3/8 in. by 2 1/4 in.
256 perforations from 121 ft. to 141 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? driller
Yield: 200 gal./min. with 21 ft. drawdown after 2 hrs.
400 " " 40 " " 2 "
" " " " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 8 sacks
How was cement grout placed? poured in from the top
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel: ft.
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Marion Driller's well number 2189
1/4 Section 35 T. 5S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 48 ft.
Static level 30 ft. below land surface. Date 12/1/78
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing
Depth drilled 144 ft. Depth of completed well 144 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Topsoil	0	2	
Brown Clay	2	41	
Blue Clay	41	48	
Black Sand	48	64	
Blue Sticky Clay	64	68	
Blue Sandy Clay	68	79	
Sticky Blue Clay	79	102	
Gray Clay	102	118	
Black Sand and Gravel	118	141	
Blue Clay	141	144	

Work started 11/27/78 19 Completed 12/1/78 19
Date well drilling machine moved off of well 12/2/78 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Dallas L. Beis Date 12/2/78, 19...
(Drilling Machine Operator)
Drilling Machine Operator's License No. 752

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Willamette Drilling Co.
(Person, firm or corporation) (Type or print)
Address 73650 Neill Rd. NE Salem, OR 97303
[Signed] Dallas L. Beis
(Water Well Contractor)
Contractor's License No. 561 Date 561, 19...