## NOTICE TO WATER WELL CONTRACT The original and first copy in of this report are to the filed with the

Gravel placed from .....

STATE OF OREGON

STAT

within 30 days from the date of well completion. The CIVICE ON OREGON	e or print) State Permit  (5 5 1 2 7	No		
(1) OWNED.	(11) LOCATION OF WELL:			
(1) OWNER:	County Marion Driller's well number 1415			
Name James Moullet				W.M.
Address kt. 1 Box 143, Gervais, Oregon	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):				
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	Also Sec 2-3 in Twp. 58 xange 2W			
If abandonment, describe material and procedure in Item 12.	7,7,7,0			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of we			
Rotary Driven Domestic Industrial Municipal				
Cable				
CASING INSTALLED: Threaded  Welded  \text{T} \text{ Welded } \text{T} \text{ Gage } 250	Formation: Describe color, texture, grain size and structure of materials and show thickness and nature of each stratum and aquifer penetrated with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates			
" Diam. from ft. to ft. Gage	MATERIAL	From	То	SWL
" Diam. from ft. to ft. Gage	Top soil	_0_	2	
	Yellow Clay	2	10	
PERFORATIONS: Perforated? ♥ Yes □ No.	Blue clay	10	65	
Type of perforator used Mills	Black sand	65	81	
Size of perforations $\frac{1}{2}$ in. by $2\frac{1}{2}$ in.	Gray clay	81	100	
240 perforations from 113 ft. to 130 ft.	racked brown sand	100	110	
540 perforations from 163 ft. to 195 ft.	Brown sand and gravel	110	130	
perforations from ft. to ft.	Blue clay	130	145	,
perforations from ft. to ft.	Black sand	145	160	
perforations from ft. to ft.	Black sand and gravel	160	195	
(E) CODESIGN.	Black sand	195	210	
(7) SCREENS: Well screen installed?   Yes  No	Cemented gravel	210	215	ļ
Manufacturer's Name TypeModel No				-
Diam. Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.				
(8) WATER LEVEL: Completed well.				
Static level 36 ft. below land surface Date 7-15-69				
sian pressure lbs. per square inch Date				
(9) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? ✓ Yes □ No If yes, by whom? priller	Work started July 1. 1969 Com	pleted 7117.	v 15.	10180
yield: 300 gal./min. with 1 ft. drawdown after 3 hrs.	Date well drilling machine moved off of well July 15, 1969 19			
# 500 " 6 " 3 "  ***SEAR* test 600 gal./min. with 9 ft. drawdown after 3 hrs.	Drilling Machine Operator's Certificati This well was constructed under m rials used and information reported a knowledge and belief.	on: y direct sur	ervision	. Mate
Artesian flow g.p.m. Date  Temperature of water Was a chemical analysis made?  Yes  No	[Signed] Bond Monton Date 7-15-69, 19			
(10) CONSTRUCTION:  Well seal—Material usedDrill cuftings PuddleClay	Drilling Machine Operator's License No536			
Depth of seal	Water Well Contractor's Certification:  This well was drilled under my jurisdiction and this report true to the best of my knowledge and belief.			
Were any loose strata cemented off? Tyes \( \) No Depth	NAME WILLAMETTE DRILLING COMPANY (Type or print)			
Did any strata contain unusable water?	Address 7641 35th Ave. NE Salem, Oregon 97303			
Method of sealing strata off  Was well gravel packed? ☐ Yes ☑ No Size of gravel:ft.	[Signed] (Water Well Contractor)  Contractor's License No			