

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

LINGI WATER WELL REPORT

		ř	_	12		.'2	_	L
State	Well	No.	5	1 2	يبا	<u> </u>	2	r

•		
STI A ME	ENGINEER, SALEM, ORI	CON 97310
DIWIE	ENGINEER, DESCRIPTION	20,021,0.020
	within 30 days from the d	ate
	Within do days in our care a	

filed with the	State Well No.	20-			
STATE ENGINEER, SALEM, OREGON 97310 STATE OF Within 30 days from the date (Please type					
of well completion.	Orandown is amount w	ater leve	l is		
(1) OWNER: JAMES C.PHILLIPS	Was a pump test made? Yes \(\bar{\text{No}} \) No If yes, by whom:	er.			
Name JAMES C.IIIIIIIII Address RT.I BOX I58 GERVAIS, OREGON.	Yield: 350 gal./min. with 62 ft. drawdown	ı after	4 hrs.		
Address RI • I BOX 100 GENTALES CHECKEN	" 280 " 4 2 "		4 "		
(2) LOCATION OF WELL:	<u>" 225 " 32 " </u>		4 "		
	Bailer test gal./min. with ft. drawdov	vn after	hrs.		
County MATCLES 35 m 5 5 m 2 W WM	Artesian flow g.p.m. Date Temperature of water Was a chemical analysis m	ade2 🗆 3	Zes □ No		
14 14 Section OO T. OO R. OW W.M. Bearing and distance from section or subdivision corner	10mporus				
Bearing and distance from section of sabarrason corner	(12) WELL LOG: Diameter of well below cas	ing			
	Depth drilled I20 ft. Depth of completed well				
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each characteristics.	and stru re materi ange of	cture, and lal in each formation.		
	MATERIAL	FROM	ТО		
(3) TYPE OF WORK (check):	TOP SOIL	0	3		
New Well ■ Deepening □ Reconditioning □ Abandon □	BROWN SILT	3	39		
bandonment, describe material and procedure in Item 12.	BLHE CLAY	39	50		
(4) PROPOSED USE (check): (5) TYPE OF WELL:	BLACK SAND	50	63		
Rotary □ Driven □	GRAY CLAY	63	90 96		
Cable A Jetted	BROWN SAND SMALL	90 96	102		
Dug [] Dorock []	BROWN SAND SMALL GRAV				
	BIACK SAND & LARGE GRAVEL	IIO	120		
" Diam. from ft. to ft. Gage	10 10 10 10 10 10 10 10 10 10 10 10 10 1				
		<u> </u>			
(7) PERFORATIONS: Perforated? Yes No		 			
Type of perforator used MILLS					
Size of perforations 2 in. by 3/8 in.		 			
perforations from IO7 ft. to IZO ft.					
perforations from ft. to ft.					
perforations from ft. to ft.		 	<u> </u>		
perforations from ft. to ft.		-	 		
(8) SCREENS: Well screen installed? ☐ Yes ▼No		-	<u> </u>		
Manufacturer's Name					
Model No.		-			
m Slot size Set from ft. to ft.	Work started JUNE 9 1966 Completed JU				
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well JUNE	<u> 17</u>	19 6		
(9) CONSTRUCTION:	(13) PUMP:				
Well seal-Material used in seal CEMENT & PUTTLE CLAY	Manufacturer's Name				
Well seal—Material used in seal	Type:	н.р			
Depth of sealft. Was a packer used?in.	Water Well Contractor's Certification:				
Were any loose strata cemented off? TYes No Depth					
Was a drive shoe used?▼ Yes □ No	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	and this	s report is		
Was well gravel packed? Yes Size of gravel:	WITH A MEMBERS OF THE TRIC OF				
Gravel placed fromft. toft.	NAME WILLAMETE DRILLING CO (Person, firm or corporation) (Type or print)				
Did any strata contain unusable water? Yes No	Address RT.2 BOX 276 SALEM, ORE	ON.			
Type of water? depth of strata Method of sealing strata off	Duilling Machine Countries Viscous No.	170			
(10) WATER LEVELS:	Drilling Machine Operator's License No.	<u>Y</u>			
(10) WATER LEVELS:	[Signed] (Water Well Contractor)		•••••		
Static level 28 ft. below land surface Date 6/16/66		17	., 66		
Artesian pressure lbs. per square inch Date	Contractor's License No Date		, 19		