M ARI. 2580

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be 1110 U 1966 WATER WELL REPORT filed with the

36 D
State Well No. 5/2w-76

State Permit No.

med with the	· ·	E limbe d
STATE ENGINEER SALEM OREGON-97910	CONTROL OF THE OF	OREGON COCO P
within 30 days from the date	ENGINE Emplease type	or print)
STATE ENGINEER, SALEM, OREGON 97810 within 30 days from the date of well completion.	OPECON COME	

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water lowered below static level	level is
Name JAMES MOULLET	Was a pump test made? K Yes 🗆 No If yes, by whom?	
Address RT. I BOX 198	Yield: 350 gal./min. with 33 ft. drawdown after	
GERVAIS , OREGON	<u> </u>	26 "
(2) LOCATION OF WELL:	" "	
County MARION Driller's well number II40	Bailer test gal./min. with ft. drawdown as	fter hrs.
14 14 Section 26 T. 35-36. 2 W.M.	Artesian flow g.p.m. Date	
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis made?	☐ Yes ☐ No
searing and distance from Section of Sabatashon Collies	(12) WELL LOG: Diameter of well below casing	
	Depth drilled I40 ft. Depth of completed well I4	lO ft.
·		
	Formation: Describe by color, character, size of material and show thickness of aquifers and the kind and nature of the mostratum penetrated, with at least one entry for each change	terial in each
(3) TYPE OF WORK (check):	MATERIAL FRO	
Yeav Well \(\bar{\text{\text{T}}} \) Deepening \(\bar{\text{\tin}\text{\texi\text{\texi\text{\text{\text{\texi}\text{\text{\texi}\text{\text{\text{\text{\text{\texi}	TOP SOIL BROWN SANDY SOIL	
bandonment, describe material and procedure in Item 12.		
	BLUE CLAY 4	
(4) PROPOSED USE (check): (5) TYPE OF WELL:	GRAY CLAY 62 BLACK SAND 99	
Oomestic ☐ Industrial ☐ Municipal ☐ Rotary ☐ Driven ☐	BLACK SAND & GRAVEL IC	
rrigation Test Well Other Dug Bored		
(a) Cacric Tigmat I III		[5 II9 19 135
Threaded Welded TY TOP ft. to 140 ft. Gage 250		35 I40
	BLUE OHAT	75 140
"Diam. from		_
" Diam. from ft. to ft. Gage		
(7) PERFORATIONS: Perforated? XYes No		
Type of perforator used MILLS		
Size of perforations 2 in. by 3/8 in.		
380 perforations from IIO ft. to I35 ft.		
perforations fromft. toft.		
perforations from ft. to ft.		
perforations from ft. to ft.		
(8) SCREENS: Well screen installed? Yes No		
Manufacturer's Name		
Model No.		
Diam Slot size Set from ft. to ft.	Work started MAY 3 1966 Completed MAY I	9 T986
Diam Slot size	Date well drilling machine moved off of well MAY IS	
(9) CONSTRUCTION:	(13) PUMP:	
TAVE STANTING S. TOTTOTAL CTAV	(10) 1 0.1111.	
Well seal—Material used in seal CEMENT & PUDDLE CLAY	Manufacturer's Name	
Depth of seal ft, was a packer used?	Type:	
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:	
Were any loose strata cemented off? ☐ Yes ☐ No Depth		_
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	This well was drilled under my jurisdiction and the true to the best of my knowledge and belief.	is report is
Gravel placed fromft. toft.	IN TO TAXABORDED TO THE TRACE AND	
Did any strata contain unusable water \(\subseteq \text{Yes} \subseteq \text{No} \)	NAME WILLAMETTE DRILLING CO (Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address RT. 2 BOX 276 SALEM, OREGON	
Method of sealing strata off		****************
(10) WATER LEVELS:	Drilling Machine Operator's License No. 470	**********
<u></u>	[Signed] Comil (O. Beiler)	
Static level 27 ft. below land surface Date 5/18/60	(Water Well Contractor)	****************
Artesian pressure lbs. per square inch Date	Contractor's License No. 2 Date MAY IS I	966 ₁₉

(USE ADDITIONAL SHEETS IF NECESSARY)