

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

2884
MAR 11 1968

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED
DEC 25 1967
State Well No. 5/3w-1
STATE ENGINEER
SALEM OREGON
State Permit No.

(1) OWNER:

Name RIVER BEND FARM
Address Star Route Box 20C St. Paul, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
12" Diam. from 0 ft. to 20 ft. Gage .25
6" Diam. from 0 ft. to 146 ft. Gage .25
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name Rosco Moss
Type Louvered-full Flow Model No.
Diam. 6 Slot size 1/16 Set from 146 ft. to 166 ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level ft. below land surface Date
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? Driller
Yield: 60 gal./min. with 120 ft. drawdown after 2 hrs.
30 " " 100 " " 2 "
" " " " " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water 51 Was a chemical analysis made? Yes No

(10) CONSTRUCTION:

Well seal—Material used Bentonite
Depth of seal 20 ft.
Diameter of well bore to bottom of seal 15 in.
Were any loose strata cemented off? Yes No Depth
Was a drive shoe used? Yes No
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel 1/16 x 1/8
Gravel placed from 0 ft. to 166 ft.

(11) LOCATION OF WELL:

County Marion Driller's well number 1967-51
1/4 1/4 Section I T. 5 S R. 3W W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 6"
Depth drilled 166 ft. Depth of completed well 166 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
Top soil	0	3	
Clay, Brown sandy	3	33	
Clay, Blue	33	67	
Clay, Blue, sandy	67	88	
Sand, Black, Medium	88	95	
Boulder	95	96	
Clay, Brown	96	99	
Clay, Blue	99	107	
Clay, Brown	107	112	
Clay, Blue	112	120	
Clay, Grey, Sandy	120	124	
Clay, Brown Sandy, medium	124	150	
Gravel, Medium with Black sand			
Med. to coarse	150	166	
			67

Work started Nov. 21 1967 Completed Dec. 1 19 ~~67~~
Date well drilling machine moved off of well Dec 1 1967

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Marvin D. Skyles Date Dec 9, 1967
(Drilling Machine Operator)

Drilling Machine Operator's License No. 224

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME SKYLES DRILLING & SUPPLY
(Person, firm or corporation) (Type or print)

Address GLADSTONE, OREGON

[Signed] George J. Skyles
(Water Well Contractor)

Contractor's License No. 58 Date 12-6, 1967