NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

2900

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED JUN 12 1968 STATE ENGINEER SALEM OREGON

State Well No. 5/3w-12
State Permit No. 6-8868

(1) OWNER:
Name Mel Hansen
Address Rt. 1 Box 277 Berries, Ore

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☑ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:
Threaded ☐ Welded ☑
12" Diam. from 0 ft. to 130 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? ☑ Yes ☐ No.
Type of perforator used Mills Knife
Size of perforations 5/16 in. by 2 in.
432 perforations from 101 ft. to 119 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.
Static level 55 ft. below land surface Date 5-21-68
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☑ Yes ☐ No If yes, by whom?
Yield: 218 gal./min. with 26 ft. drawdown after 2 hrs.
" with air lift " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? ☐ Yes ☐ No

(10) CONSTRUCTION:
Well seal—Material used Bentonite
Depth of seal 20 ft.
Diameter of well bore to bottom of seal 15 in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☐ Yes ☒ No
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:
County Marion Driller's well number
¼ ¼ Section 12 T. 5S R. 3W W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG:
Diameter of well below casing 12
Depth drilled 156 ft. Depth of completed well 130 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
top soil	0	6"	
brown clay	6"	25'	
brown silt	25	38	
blue clay	38	65	
blue silt	65	67	
black sand	67	77	
brown sandy clay	81	96	
red sand & gravel, no 2"	96	119	
brown clay (light)	119	126	
brown clay	126	138	
blue silty clay	138	151	
brown sand	151	156	
gravel	156		

Work started 5-8 1968 Completed 6-3 1968
Date well drilling machine moved off of well ~~5-21~~ 6-3 1968

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Roger J. Mullen (Drilling Machine Operator) Date 6-4, 1968
Drilling Machine Operator's License No. 581

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME Mike Schneider (Person, firm or corporation) (Type or print)
Address Star Rt. Box 97 St Paul Ore
[Signed] Mike Schneider (Water Well Contractor)
Contractor's License No. 389 Date 6-4, 1968

(USE ADDITIONAL SHEETS IF NECESSARY)