

The original and first op of this report are to filed with the MLR 201969 STATE OF OREGON STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date in the completion. (Do not write above this line)

State Well No. 5/3W -36

State Permit No.

(1) OWNER:	(11) LOCATION OF WELL:			
Name Les PEARMINE	County MARION Driller's well number			
Address RT. / BOX 50	14 14 Section 36 T. 55 R. 3W W.M.			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well below casing 15			
Rotary Driven Driven Towards T	The state of the s			
Cable 20 Jetted Domestic Industrial Municipal Dug Bored Irrigation 2 Test Well Other	Depth drilled 165 ft. Depth of completed well 165 ft.			
CASING INSTALLED: Threaded Welded A	Formation: Describe color, texture, grain size and show thickness and nature of each stratu with at least one entry for each change of form in position of Static Water Level as drilling pro-	m and ac	quifer per	netrated,
" Diam. from ft. to ft. Gage	MATERIAL	From	To To	SWL
" Diam. from ft. to ft. Gage	TOPSOIL			3WL
DEDEODATIONS.	CLAY YELLOW COLOR	0	2	
PERFORATIONS: Perforated? Yes No.	SAND FINE BROWN	2 48	57	
Type of perforator used MILLS	CLAY BROWN COLOR	インフ	60	
Size of perforations 3/g in. by 2 2 in.	SAND BROWN FINE	60	7/	
480 perforations from 130 tt. to 152 tt.	CLAYSTON BLUE	7/	78	
perforations from ft. to ft.	CHAYSTONE BROWN	78	80	
perforations from ft. to ft.	CONGLOMERATE	90	102	·
perforations from ft. to ft.	CLAY BLUE- SANDY	102	114	
perforations from ft. to ft.	CONGLOMERATE	1/4	128	
(7) SCREENS: Well screen installed? \(\sigma\) Ves \(\frac{1}{2}\) No	GRAVEL & SAHDI'L W.B	128	129	
200 200	CONGLO MERATE	129	139	
Manufacturer's Name Type Model No	GRAVELI SAND 1'- W.B	139	140	7115"
Diam. Slot size Set from ft. to ft.	CONGLONERATE	140	151	#
Diam. Slot size Set from ft. to ft.	GRAVEL & SAND 75% SAND	151	154	715
Set from It. to	CLAYSTONE GRAY FIRM	154	165	
(8) WATER LEVEL: Completed well.				
Static level 7/5" ft. below land surface Date 2-2269				
sian pressure lbs. per square inch Date				
(9) WELL TESTS: Drawdown is amount water level is	A STATE OF THE STA			
lowered below static level STOTTLER	2000		·	
Was a pump test made? Yes \(\subseteq No \text{ If yes, by whom?} \)	0 10			
Yield: 500 gal./min. with 25 ft. drawdown after hrs.	Work started 2-/9- 1969 Complete	d 62.	27.	1969
. 580 " 30 " 3"	Date well drilling machine moved off of well	2-	27-	19 6 F
" 706 " 35" " 1"	Drilling Machine Operator's Certification:			
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my div	ect supe	rvision.	Mate-
Artesian flow g.p.m. Date	rials used and information reported above knowledge and belief.	e are tr	ue to m	y best
	1 1 mm 1 1 1 7 1 1 1 1 1 1 1 1 1 1 1 1 1	っ	.47	10
Temperature of water Was a chemical analysis made? Yes No	[Signed] (Drilling Machine Operator)	Date Z	-2/-	19
(10) CONSTRUCTION: Well cool Metavial word PUDDLED CLAY	Drilling Machine Operator's License No	187	,	
Well seal-Material used				-
Depth of sealft.	Water Well Contractor's Certification:			
Diameter of well bore to bottom of seal in.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Were any loose strata cemented off? Tyes No Depth	NAME J. A. SNEED & SONS (Person, firm or corporation) (Type or print)			
Was a drive shoe used? ZYes □ No Did any strata contain unusable water? □ Yes □ No	(Person, firm or corporation) (Type or print)			
	Address 3910 SILVERTON P.D. STLER ORE			
Type of water SAHDY depth of strata 102 70114	CO P			
Method of sealing strata off CMSED	[Signed] Kir, Succes			
Was well gravel packed? Yes No Size of gravel:	(Water Well Contracte			
Gravel placed from ft. to ft.	Contractor's License No. 6 Date	1-27.		. 69
TICE ADDITIONAL OF		***********	, l	o'