## File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

## WATER WELL REPORT STATE OF ORFO

	11	,	^
State Well No.	6/1W-		 Z

C 22 State Permit No. ......

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level			
Name Ray Knori	Was a pump test made? ☐ Yes 🏅 No If yes, by whom?			
Address Rte. 1, Box 21	Yield: gal./min, with ft. drawdown after	hrs.		
Mt.Angel, Oregon	" "	17		
(2) LOCATION OF WELL:	n n	**		
County Marion Owner's number, if any—	Bailer test 35 gal./min. with 90 ft. drawdown after	1 hrsX		
W.M.	Artesian flow g.p.m. Date			
Bearing and distance from section or subdivision corner	Temperature of water XX Was a chemical analysis made?   Ye	s 🗷 No		
1575 ft. east & 250 ft. north from S.	(19) WELL LOC.			
corner of section 1, T.6 S., R.1 W.	Diameter of weil	inches.		
of W.M.				
	Formation: Describe by color, character, size of material and struc show thickness of aquifers and the kind and nature of the materia stratum penetrated, with at least one entry for each change of fe	cure, and al in each		
	1			
	MATERIAL FROM	TO		
(3) TYPE OF WORK (check):	Top soil- brown Q	2		
New Well 🖺 Deepening 🗌 Reconditioning 🗎 Abandon 🗆	Clay - brown 2	20		
if spandonment, describe material and procedure in Item 11.	Clay-brown & small boulders 20	23		
ADDODOGED TICE (-LL). (E) MYDE OF WELL.	Clay- brown 23	41		
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Conglomerate-gray, waterbear   ng41	49		
Domestic 🖫 Industrial 🗌 Municipal 🗎 Rotary 📮 Driven 🗍 Cable 🔁 Jetted 🗍	Clay-gray 49	70		
Irrigation 1 Test Well   Other   Dug   Bored	Conglomerate-gray, waterbrg. 70	75		
	Clay- blue 75	87		
(6) CASING INSTALLED: Threaded [], WeldedXX	Clay-lavender 87	109		
E "Diam from tt to 102 77 Gage • 250x	Sand-gray, waterbearing, 109	114		
6 " Diam. from 0 ft. to 110 ft. Gage • 250	Clay- gray 114	140		
" Diam. from ft. to ft. Gage				
	,			
(7) PERFORATIONS: Perforated?   Yes X No	SEE DEEPENING (7-16-66)			
Type of perforator used	THE CERTONIAS IT IS NOT			
SIZE of perforations in. by in.				
perforations from ft. to ft.				
perforations from ft. to ft.				
perforations from				
perforations from ft. to ft.		····		
perforations fromft. toft.				
(8) SCREENS: Well screen installed  Yes XXNo				
(8) SCREENS: Wen seree				
Manufacturer's Name Model No.				
**				
Slot size Set from ft. to ft.  Slot size Set from ft. to ft.		11. (7		
Slot size Set Holling 10. to	Work started Sept.19, 161. Completed Sept. 2	(4 月9)上		
(9) CONSTRUCTION:	(13) PUMP:			
Was well gravel nacked? M Yes   No Size of gravel: # 2 I'C.	Manufacturer's Name Universal			
Gravel placed from 140 ft to 110 ft	Type: Submersible HP.	2		
Was a surface seal provided? X Yes \( \text{No_To what depth?} \) ft.	Type:			
Material used in seal— Puddled clay	Well Driller's Statement:			
Did any strata contain unusable water? Yes 🖔 No	This well was drilled under my jurisdiction and this r	enort in		
Type of water? Depth of strata	true to the best of my knowledge and belief.	eport is		
Method of sealing strata off	TO CHARACTER CT			
	NAME R. SUCCELL & SONS (Person, firm, or corporation) (Type or print			
(10) WATER LEVELS:	Address Rte. 3, Box 169, Silverton, Oregon			
Static level 45 ft. below landsurface Date 9/24/61	Audicos	00		
Artesian pressure lbs. per squire inch Date	Driller's well number			
T A	0108+11.			
Log Accepted by:	[Signed] Jaul S. Bladell			
[Signed] 19 19	(Well Driller) License No. 296 Date June 20	61		
(Owner)	License No. 290 Date 30110 20	, 19. <sup>C) L</sup>		
<u>-</u>	•			

in the state of the second