JUN 1 8 1975 tate Well No. 65/1W-4 aa of this report are to be filed with the STATE OF OREGON STATE ENGINEER, SALEM, OREGON 97310 STATE ENGINEER Permit No. (Please type or print) within 30 days from the date (Do not write above this line) of well completion. SALEM. OREGON (10) LOCATION OF WELL: (1) OWNER: County Marion Driller's well number Name Elmer Esch N.E. 14 N.E. Section 4 т.63 R. 1W Address Rt. 1. Box 188 Mt.Angel OR 97362 Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well Reconditioning [ Abandon 🗌 Deepening [ If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Driven 🔲 Rotary ft. below land surface. Date 5/1/75 Domestic | Industrial | Municipal | Static level Cable Jetted [ Irrigation 2 Test Well Other Bored | lbs. per square inch. Date Dug Artesian pressure CASING INSTALLED: Threaded [ Welded 2 (12) WELL LOG: Diameter of well below casing ... 10 " Diam. from 1 + ft. to 157 ft. Gage 250 ft. Depth of completed well Depth drilled 260 " Diam. from ...... ft. to ..... ft. Gage ...... Formation: Describe color, texture, grain size and structure of materials; " Diam. from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Gage ..... and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? 
Yes No. MATERIAL Type of perforator used Top Soil brn. 0 2 Size of perforations in. by Clay-brn. 2 perforations from ...... ft. to ..... ft. 45 \_\_\_ perforations from ......ft. to Medium Congl. Brn 45 Layers of basalt with blue53 perforations from ...... ft. to .. clav (7) SCREENS: Well screen installed? 
Yes No Clay brn 80 94 Manufacturer's Name ..... 94 Clay rusty brn 124 Layerws of Basalt with 124 Diam. ..... Slot size ..... Set from .... grev clav Diam. Slot size ..... Set from .... Basalt grey crevicy 150 157 Drawdown is amount water level is lowered below static level Reselt grey hard 157 168 (8) WELL TESTS: Basalt grey and brn seamy168 Was a pump test made? 
Yes To No If yes, by whom? Rasalt grey hard 174 187 Baselt brn grey weathered 187 hrs. gal./min. with ft. drawdown after Yield: Basalt greyhard 204 240 (W.B.) Basalt brn and grey poucus40 246 360 10 MIn". Mir Basalt grey crevicy hard 246 W.B. 540 gal./min. with 178 ft. drawdown after 1 hrs. **Bekex** test Artesian flow Depth artesian flow encountered ...... ft. Work started 3/25/75 19 perature of water Date well drilling machine moved off of well 5/1/75 (9) CONSTRUCTION: Drilling Machine Operator's Certification: Cement Well seal-Material used This well was constructed under my direct supervision. Materials used and information reported above are true to my Well sealed from land surface to ....Approx. Diameter of well bore to bottom of seal \_\_\_\_\_\_14 best knowledge and belief, Stateli Date 6 13 197 Diameter of well bore below seal ..... (Drilling Machine Operator) Number of sacks of cement used in well seal ...... Drilling Machine Operator's License No. 860 Number of sacks of bentonite used in well seal ...... sacks Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name R. Stadeli & Sons, Inc.

(Type or print) Was a drive shoe used? Tyes No Plus ...... Size: location ...... ft. Did any strata contain unusable water? 🗌 Yes 😿 No Box 169 Silverton, OR Type of water? Method of sealing strata off Was well gravel packed? 

Yes No Size of gravel: ..... Contractor's License No. 296 Date 5-3-75, 19 #. to .....

NOTICE TO WATER WELL CONTRACTOR
The original and first copy

RECEIVED