NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

DEC 14 WATER WELL REPORT 196 STATE OF OREGON (Please type or print)

G3458

State Well No. ...

State Permit No. ..

(1) OWNER: Name John Singler Address Rte.1, Box 183	(11) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? Yield: Property of the		
Mt.Angel,Oregon	" gai./mm. with ft. drawdo	wn after	hrs.
(2) LOCATION OF WELL: County Marion Driller's well number	Bailer test gal./min. with 13 ft. drawdo	wn after	1 "
1/4 1/4 Section T. R. W.M.	Temperature of water Was a chemical analysis	made? 🗍	Yes X No
Bearing and distance from section or subdivision corner 2400 ft. south & 1200 ft. west from N.E.corner of section 4, T.6 S., R.1 W.	(12) WELL LOG: Diameter of well below or the Depth drilled 177 ft. Depth of completed w	asing 61	11
of W.M.	Formation: Describe by color, character, size of materia show thickness of aquifiers and the kind and nature of stratum penetrated, with at least one entry for each of the color of the co	al and stru	t ft. acture, and ial in each formation.
	MATERIAL	FROM	то
(3) TYPE OF WORK (check): Well ★ Deepening □ Reconditioning □ Abandon □	Top soil brown	0	2
If abandonment, describe material and procedure in Item 12. (4) PROPOSED USE (check): (5) TYPE OF WELL:	Clay brn.	2	10
Domestic A Industrial Municipal Rotary Driven Cable Jetted	Boulders grey brn.	10	14
	Med conglomerate grey	14	48
6 CASING INSTALLED: Threaded Welded Welded Display Diam. from 8 2 bove to 48 -05 ft. Gage • 250	Hard basalt rock grey, fract.	48	98
	Clay seam soft grey	98	99
(7) PERFORATIONS: Perforated? ☐ Yes ★ No Type of perforator used	Hard basalt grey fractured	99	177
Size of perforations in. by in. perforations from ft. to ft. perforations from ft. to ft.	All water coming in rock		
(8) SCREENS: Well screen installed? Well screen installed? Yes X No Manufacturer's Name Model No.			
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	Work started 7/20 1964. Completed 8/19	/10	19 6 4
(9) CONSTRUCTION: Well seal—Material used in seal Concrete & Bentonite Depth of seal ft. Was a packer used? no Diameter of well bore to bottom of seal in.	(13) PUMP: Manufacturer's Name Type: H.P.		
Were any loose strata comented off Var ves \(\text{No} \) No Depth 30 to 95 Was a drive shoe used? \(\text{XYes} \) No Was well gravel packed? \(\text{Yes} \) No Size of gravel:	Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Gravel placed fromft. toft. Did any strata contain unusable water? Type of water? Depth of strata	NAME R. Stadeli & Sons (Person, firm or corporation) (Type or print) Address Rt 3 Box 169, Silverton, Oreg.		
Method of sealing strata off		•	_
(10) WATER LEVELS: Static level 62 ft. below land surface Date 8/10/64 Artesian pressure lbs. per square inch Date	[Signed] Contractor's License No. 296 (Water Well Contractor) Contractor's License No. Date		1964
(USE ADDITIONAL SH			-, 40