WATER WELL REPORT 125 1975 of this report are to be State Well No. 65/14-5 filed with the STATE OF OREGON (Please type of MATE) R RESOURCES DEPT.
State Permit No. ....... STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date (Do not write above this find EM. OREGON of well completion. (1) OWNER: (10) LOCATION OF WELL: Name Tom Ewing Driller's well number Marion 3289 Cheyenne Court NW 5 1/4 Section T. 6 1W W.M. Salem, Oregon Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well DX Deepening [ Reconditioning [ Abandon | If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Driven [ Domestic 🗌 Industrial 🗎 Municipal 🗇 Static level 17 ft. below land surface. Date 7-15-75 Jetted 🗆 Bored | Dug Irrigation X Test Well | Other Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded [] Welded [4] (12) WELL LOG: Diameter of well below casing ..... £10, Diam. from top ft. to 278 ft. Gage 250 Depth drilled ft. Depth of completed well 300 Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? X Yes No. Mills Type of perforator used MATERIAL From То SWT. Size of perforations 7/16 in. by 2 3/4 in. Top Soil 0 2 1250 perforations from 95 ft. to 215 ft. Yellow Clav 2 25 Blue Clay 25 45 perforations from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Brown Sand 45 50 Blue Clay 50 60 (7) SCREENS: Well screen installed? ☐ Yes 🖼 No Black sand 60 70 Manufacturer's Name ..... Blue Clay 70 90 ...... Model No. ..... Cemented gravel 90 215 Diam. Slot size Set from ft. to ft. Blue Clay 215 240 Diam. Slot size Set from ft. to ft. Cemented gravel 240 260 Blue Clay 260 300 Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made? ▼ Yes □ No If yes, by whom? Driller Yield: 300 gal./min. with 23 ft. drawdown after 9 hrs. 400 28 same " 500 38 same " 600 gal./min. with ft. drawdown after samehrs. Bailer test Artesian flow Depth artesian flow encountered ..... ft. pperature of water Work started May 13, 19 75 Completed July 15, 75 19 Date well drilling machine moved off of well July 16. 1975 19 (9) CONSTRUCTION: **Drilling Machine Operator's Certification:** Well seal-Material used ..... This well was constructed under my direct supervision. Materials used and information reported above are true to my Diameter of well bore to bottom of seal \_\_\_\_\_\_in. best knowledge and belief. [Signed] Ronald W. Morton. Date 7-16-75, 19.... Diameter of well bore below seal .......10..... in. Drilling Machine Operator's License No. .... 536 Number of sacks of bentonite used in well seal \_\_\_\_\_\_ sacks Brand name of bentonite ..... Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is \_\_\_\_\_ lbs./100 gals. true to the best of my knowledge and belief. Name WILLAMETTE DRILLING COMPANY

(Type or print)

(Type or print) Was a drive shoe used? To Yes I No Plugs \_\_\_\_ Size: location \_\_\_\_ ft. Did any strata contain unusable water? 

Yes X No Address XXXX 35THXXXXX MXX Salem, Oregon 97303 depth of rata Type of water? [Signed] (Water Well Contractor) Method of sealing strata off Was well gravel packed? 

Yes 
No Size of gravel: Contractor's License No. .2 Date .....7-16-75 19..... Gravel placed from ..... (USE ADDITIONAL SHEETS IF NECESSARY) SP\*45656-119

RELEIVEU

NOTICE TO WATER WELL CONTRACTOR

The original and first copy