NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be STATE OF OREGON STATE ENGINEER, SALEM, OREGON 973DEC - 3 1975 (Please type or print) within 30 days from the date of well completion. WATER RESOURCES DEPT. State Permit No. SALEM, OREGON (10) LOCATION OF WELL: (1) OWNER: Driller's well number Marion Name William Jebousek 1/4 Section Address 10601 Howell Prarie Road NE 6 Salem. Oregon Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Abandon [1] New Well 🔀 Deepening [Reconditioning [If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): (3) TYPE OF WELL: Depth at which water was first found Rotary Driven [] ft. below land surface. Date 17-29-75 Domestic 📆 Industrial 🗌 Municipal 🗍 Static level Jetted □ Cable X. Irrigation

Test Well
Other Bored | Dug lbs. per square inch. Date Artesian pressure CASING INSTALLED: Threaded [Welded [] (12) WELL LOG: Diameter of well below casing " Diam from top ft to 145 ft. Gage 250 Depth drilled ft. Depth of completed well " Diam. from _____ ft. to _____ ft. Gage ____ Formation: Describe color, texture, grain size and structure of materials; " Diam. from ft. to ft. Gage ... and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? Yes No. MATERIAL Type of perforator used 55 n in. by Top Soil Size of perforations 55 90 perforations from ft. to Brown sand 9.0 105 Blue Clay perforations from ft. to Black Sond 105 128 perforations from _____ ft. to ___ 128 7.47 Gray Clay (7) SCREENS: Well screen installed? Yes No Black sand and Gravel 141 145 Manufacturer's Name Diam. Slot size Set from ft. to Diam. Slot size Set from ____ ft. to ft. Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made?
Yes Mo If yes, by whom? gal./min. with ft. drawdown after hrs. Yield: ,, ,, gal./min. with 15 ft. drawdown after Bailer test Artesian flow g.p.m. Depth arfesian flow encountered Work started 11-24-75 Completed 11_29_75 19 perature of water 19 Date well drilling machine moved off of well 11-29-75 19 (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used Cement This well was constructed under my direct supervision. Well sealed from land surface to20.______ft. Materials used and information reported above are true to my Diameter of well bore to bottom of sealin. best knowledge and belief. [Signed] Qually Monton Date 12-1-75, 19.... Diameter of well bore below seal ______6.... in. Number of sacks of cement used in well seal ________ sacks Drilling Machine Operator's License No. 536 Number of sacks of bentonite used in well seal sacks Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is lbs./100 gals. true to the best of my knowledge and belief. Was a drive shoe used? Tyes Dot Plugs Size: location ft. Name WI LAUET'E DRILLING CO PANY
(Type or print)

1450 Barnick Road NE

Contractor's License No. 2 Date 12-1-75 19

Did any strata contain unusable water?

Yes X No

Was well gravel packed? Yes No Size of gravel: ...

Type of water?

Method of sealing strata off

Gravel placed from

depth of strata