NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

TATE OF OREGON

(Do not write above This

State Permit No.

Jine	EE	NG	INEER	·	1781
ZA.L	EM	೧೯	CON	<u> </u>	6284

(1) OWNER:	(10) LOCATION OF WELL:	
Name Don M. Foster	County Marion Driller's well number 17	754
Address 4882 Lancaster Dr. NE	14 14 Section 7 T. 6S R. 1W	W.M.
Salem. Oregon	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	Dourney data distributed	
New Well   ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	•	# · · · · · · · · · · · · · · · · · · ·
If abandonment, describe material and procedure in Item 12.	(11) WARED LEVEL. Completed well	•
	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 97	ft.
Rotary   Driven   Domestic   Industrial   Municipal	Static level 45 ft. below land surface. Da	te 7_26_73
Bored   Irrigation Test Well   Other	Artesian pressure lbs. per square inch. Da	te
CACCOMO PARCEALLED.		
(5) CASING INSTALLED: Threaded □ Welded ☑	(12) WELL LOG: Diameter of well below casing	g
6 " Diam. from top ft. to 178 ft. Gage 250	Depth drilled 178 ft. Depth of completed well	178 ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure	e of materials;
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aqui with at least one entry for each change of formation. Report	fer penetrated,
(6) PERFORATIONS: Perforated? Types In No.	position of Static Water Level and indicate principal water	-bearing strata.
Type of perforator used Mills	MATERIAL From	To SWL
	_Top Soil 0	2
ble of periorations 3/8		27
320perforations from 145ft. to 178ft.		43
perforations from		60
perforations from ft. to ft.		81
(7) SCREENS: Well screen installed? ☐ Yes ☑ No		97
Manufacturer's Name		12
Type Model No.		26
Diam. Slot size Set from ft. to ft.	3 3	42
Diam Slot size Set from ft. to ft.		65
	1	78
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? A Yes No If yes, by whom? Driller		
: 80 gal./min. with 15 ft. drawdown after 5 hrs.	·	
" 100 " 25 " same "		
" 150 " 45 " same "		
" 100		
Bailer test 250 gal./min. with ft. drawdown after me hrs.		
ian flow g.p.m.	<del></del>	
remperature of water Depth artesian flow encountered ft.	Work started July 16, 1973 Completed July	•
(9) CONSTRUCTION:	Date well drilling machine moved off of well July 27,	1973 <sup>19</sup>
	Drilling Machine_Operator's Certification:	
Well seal—Material used Lement Well sealed from land surface to 20 ft.	This well was constructed under my direct s	upervision.
Diameter of well bore to bottom of seal 10 in.	Materials used and information reported above are best knowledge and belief	e true to my
	[Signed] Date _Jul	
Diameter of well bore below seal	(Drilling Machine Operator)	bayaandaadag I. Fan I. ook
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No	2
Brand name of bentonite		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of waterlbs./100 gals.	This well was drilled under my jurisdiction and true to the best of my knowledge and belief.	this report is
Was a drive shoe used? XYes No Plugs Size: location ft.		
Did any strata contain unusable water? Tes X No	Name WILLAMETTE DRITLING CO-PANY (Person, firm or corporation) (Type	or print)
Type of water? depth of strata	Address 7641 35th Ave. NE Salem, Ore	gon 97303
Method of sealing strata off	61.002	
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	[Signed] (Water Well Contractor)	
Water West Services	Contractor's License No2 DateJuly 27.	197310
Gravel placed fromft. to ft.	Date	F TA