NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

SEP = 9 1970 STATE OF OREGON
(Please type or print)
within 30 days from the das TATE ENG! No-not. Pite above this line)

SALEM. OR SON

(1) OWNER:	(10) LOCATION OF WELL:
Name Mt Angel Abbey	County Marion Driller's well number
Address St. Benedict, Oreg 97373	NE %S W % Section 11 T. 6. S R. 1W, W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well	-594_
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	
Takana M Dukan Fi	Depth at which water was first found 180 ft.
Cable Detted Define Domestic Definition of Mutual Description	Static level 113 ft. below land surface. Dat 7/16
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 19 ¹⁷
72	Depth drilled 283 ft. Depth of completed well 283 ft.
12 "Diam from 0 ft to 78 ft Gage 250 10 "Biam from 0 ft to 25" ft Gage 250	
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
" Diam. from	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Y Yes \(\square\) No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Mills Knife	MATERIAL From To SWL
Size of perforations 3/8 in, by 3 in.	Top soil brn. 0 1
#87 perforations from 180 ft. to 247 ft.	Glay brn 1 30
perforations fromft. toft.	S. Sendstone brn. 30 76
perforations fromft. toft.	H. Basalt grey 76 180
	M. mmm blk. 180 221 W.B/
(7) SCREENS: Well screen installed? \(\subseteq\) Yes \(\columbfrac{\chi}{2}\) No	H.""" grey seamy 221 253 W.B.
Manufacturer's Name	W. weathered basalt brn. 253 255 W.B.
TypeModel No.	H. basalt grey seamy 255 283 W.B.
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	
Diam. Slot size Ster Hold	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom?	
Yield: 538 gal./min. with 142 tt. drawdown after 9 hrs.	The same and the s
H H	10 25 1 Sign of a control of the con
и. — — — — и — и — и — и — и — и — и — и	
Bailer test gal./min. with ft. drawdown after hrs.	6.2. 4
Artesian flow g.p.m.	1/18/70 \$/16
mperature of water Depth artesian flow encountered X ft.	Work started 19 Completed 19
	5/ 10 /m
(9) CONSTRUCTION:	
Well seal-Material used BENTONITE	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal 10 in.	best knowledge and belief.
Diameter of well bore below seal 12 toin 250 10 to 28	[Signed] Jaw (Machine Operator) Date / 1970.
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 16
Number of sacks of bentonite used in well seal sacks	Detailed operation of intering 140.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per live salons	This well was drilled under my jurisdiction and this report is
of water Approx 100 lbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? NYes Did any strata contain unusable water? Yes No	NameR. Stadeli& Sons
	(Person, firm or corporation) (Type or print)
Type of water? depth strata	Address Silverton Oreg
Method of sealing strata off	[Signed] Jaul & Stadeli
Was well gravel packed? T Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft.	Contractor's License No. 296 Date 9 * 4/70 19
(USE ADDITIONAL SH	EETS IF NECESSARY) SP*45656-119