STATE OF OREGON

WATER WELL REPORT (as required by ORS 537.765)

RECEIVED

SEP 0 5 1985

651	IW	-11-co
Da	n e	······y····O

 	100	
 ΛΙ		
// !!	_	
NO D	י אני	
$-\omega$	/ r	

(as required by ORS 537.765) PLEASE TYPE	or PRINT IN INK WATER RESOURCES DEPTor official use only)		
(1) OWNER:	(10) LOCATION OF WEIGH PRESSED description:		
Name William Grosjacques	County Marion NE 4 SW4 of Section 14-15 of		
Address 8613 Humpert Lane NE	Township 6S Range 1W WM.		
City Mt. Angel Or. 97362 State	(Township is North or South) (Range is East or West)		
(2) TYPE OF WORK (check):	Tax Lot Lot Block Subdivision		
New Well ☐ Deepening ☒ Reconditioning ☐ Abandon ☐	(Villados)		
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLETED WELL:		
Rotary Air X Driven Domestic X Industrial Municipal D	Depth at which water was first found 190-195 ft.		
Rotary Mud Dug Irrigation Withdrawal Reinjection	Static level 168.5 ft. below land surface. Date 8-27-85		
Cable Bored Diezometric Grounding Test	Artesian pressure lbs. per square inch. Date		
(5) CASING INSTALLED: Steel Plastic	(12) WELL LOG: Diameter of well below casing 6 Depth drilled 204 ft. Depth of completed well 198 ft.		
Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of		
" Diam. from	formation. Report each change in position of Static Water Level and indicate principal		
T TAYED TATOURAY TEEN	water-bearing strata.		
LINER INSTALLED: Steel Plastic Threaded Welded	, MATERIAL From To SWL		
ft. Gauge	Basalt fract. blk 175 204 H20		
(6) PERFORATIONS: Perforated? □ Yes 耳No			
Size of perforations in. by in.	well caved in back to 198' with cuttings		
ft. to ft.	original well is very crooked		
perforations from ft. to ft.	OT IGHTER WOLL ID VELY CHOOKED		
ft. to ft.			
(7) SCREENS: Well screen installed? Yes X No			
Manufacturer's Name			
Type			
Diam. Slot Size Set from ft. to ft. Diam. Slot Size Set from ft. to ft.			
December in succession in the last in the			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes X No If yes, by whom?	Asym		
d: gal./min. with ft. drawdown after hrs.			
, , , , , , , , , , , , , , , , , , ,			
Air test 24 gal./min. with drill stem at 204 ft. 2 hrs. Bailer test gal./min. with ft. drawdown after hrs.			
Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m.			
operature of water Depth artesian flow encountered			
(9) CONSTRUCTION: Special standards: Yes \(\subseteq \) No \(\subseteq \)	Date work started 8-27-85 /completed 8-27-85		
(9) CONSTRUCTION: Special standards: Yes No Well seal—Material used Original	Date well drilling machine moved off of well 8-27-85 19		
Well sealed from land surface toft.	(unbonded) Water Well Constructor Certification (if applicable):		
Diameter of well bore to bottom of seal in.	This well was constructed under my direct supervision. Materials used and		
Diameter of well bore below seal in,	information reported above are true to my best knowledge and belief.		
Amount of sealing material sacks □ pounds □	[Signed]		
How was cement grout placed?	(bonded) Water Well Constructor Certification:		
	Bond Issued by: (Surety Company Name)		
Was pump installed? NO Type HP Depth ft. Was a drive shoe used? Yes No Pugs Size: location ft.	On behalf of West Coast Drilling-Chuck Stadeli (type or print name) (Surety Company Name) (type or print name) (Water Well Constructor)		
Did any strata contain unusable water?	This well was drilled under my jurisdiction and this report is true to the		
Type of Water? depth of strata	best of my knowledge and behef:		
Method of sealing strata off	(Signed)		
Was well gravel packed? Yes No	(Water Well Constructor)		
Gravel placed from ft. to ft.	(Dated)/ 9-3-85		