

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON
within 30 days from the date
of well completion.

3210
MARI.....

WATER WELL REPORT

STATE ENGINEER
SALEM, OREGON

STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 65/1W-16
State Permit No.

(1) OWNER:

Name Lester Harpake Jr.
Address 304 NORWAY ST. SILVERTON OR 97381

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
 Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
6" Diam. from 0 ft. to 85.9 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No

Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Bailer test 40 gal./min. with 22 ft. drawdown after 1 hrs.
Flow g.p.m.
Temperature of water 55 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite
Well sealed from land surface to 36 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 2 1/2 sacks
Brand name of bentonite NATIONAL
Number of pounds of bentonite per 100 gallons of water 200 lbs./100 gals.
Was a drive shoe used? Yes No Plug Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County MARION Driller's well number
1/4 Section 16 T. 6S R. 1W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 78 ft.
Static level 34 ft. below land surface. Date 3-2-73
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 95 ft. Depth of completed well 89 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil	0	2	
CLAY BLOCKY	2	28	
CLAY Blue	28	48	
Gravel with CLAY BLOCKY	48	66	
CLAY Blue SANDY	66	77	
Gravel CEMENT BLOCKY	77	95	34

Work started 2-27 1973 Completed 3-2 1973
Date well drilling machine moved off of well 3-2 1973

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] A.C. Stites Date 3-9, 1973
(Drilling Machine Operator)
Drilling Machine Operator's License No. 527

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name A.C. Stites (Type or print)
(Person, firm or corporation)
Address PT 3-Box 129 B. CANBY 97013
[Signed] A.C. Stites (Water Well Contractor)
Contractor's License No. 533 Date 3-9, 1973