NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State	Well No. 65/1W-18
	Permit No.

		
1) OWNER:	(10) LOCATION OF WELL:	
Name Otto Sinn	County Marion Driller's well num	ber 2268
ddress 9510 Saratoga Dr. N.E.	1/4 1/4 Section 18 T. 6S R	. 1W w.m
Silverton, Oregon 97381	Bearing and distance from section or subdivision	corner
2) TYPE OF WORK (check):		
Yew Well M Deepening □ Reconditioning □ Abandon □		
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed wel	1.
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 95	
otary Driven Domestic D Industrial D Municipal D	1	face. Date 10/15/79
Bored Irrigation & Test Well Other	Artesian pressure lbs. per square	
	massair pressure ins. per square	men. Date
**CASING INSTALLED: Threaded Welded 250 .250	(12) WELL LOG: Diameter of well bel	ow casing
	Depth drilled 220 ft. Depth of complete	•
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and	
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum	and aquifer penetrated
6) PERFORATIONS: Perforated?	with at least one entry for each change of formatio position of Static Water Level and indicate princip	n. Report each change it pal water-bearing strate
Type of perforator used Mills knife		From To SWL
Size of perforations 7/16/ in. by 3 \$3/4 in.	Topsoil	0 2
1090 perforations from 120 ft. to 218 ft.	Yellow Clav	2 30
perforations from	Blue Clay	30 70
perforations from	Sandy Yellow Clay	70 95
periorations from	Brown Sand	95 111
7) SCREENS: Well screen installed? Yes X No	Brown Sand and Gravel	111 220
Manufacturer's Name		
Type Model No.		
Diam. Slot size Set from ft. to ft.		
Diam Slot size Set from ft. toft.	RECEIVE	<u>. U </u>
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		,
	DEC-619/9	3
a pump test made? Wes No If yes, by whom? driller	WATER RESOURCES	; DEPT
gal./min. with 18 ft. drawdown after 2 hrs.	SALEM, ORES	JIA
" " "	and the last of th	
n n = n n		
er test gal./min. with ft. drawdown after hrs.		
esian flow g.p.m.		
experature of water Depth artesian flow encountered ft.	Work started 9/18/79 19 Completed	10/15/79 19
<u> </u>	Date well drilling machine moved off of well	
(9) CONSTRUCTION:		10/15/79 ¹⁹
Well seal—Material used Pourtland Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my d Materials used and information reported al	bove are true to m
Diameter of well bore to bottom of seal 14 in.	best knowledge and belief.	
Diameter of well bore below seal10	[Signed] Granda W. Morton De	ate 10/15/79, 19
Number of sacks of cement used in well see 12 sacks	Drilling Machine Operator's License No	
How was cement grout placed? powred in thru tremy pipe		MAAJ.W
The state of the s	Water Well Contractor's Certification:	
	This well was drilled under my jurisdict	ion and this report is
Was a drive shoe used? 🏿 Yes 🗌 No Plugs Size: location ft.	true to the best of my knowledge and belief	ſ.
Was a drive shoe used? X Yes \(\) No Plus \(\) No Did any strata contain unusable water \(\) Yes \(\) No	Name Willamette Drilling Co. (Person, firm or corporation)	***************************************
	Address 7365 O'Neil Rd. N.E. Sale	(Type or print)
Type of water? depth of strata	Address 1999 V Mell Ru, N.E. Sale	m, Oregon 973
Method of sealing strata off	[Signed] Dalla & Bries	
Was well gravel packed? Tes X No Size of gravel:	[Signed] Water Well Contract	or)
Gravel placed from ft.	Contractor's License No. 561 Date 10/	<u>15/79</u> , 19
(USE ADDITIONAL SH	IEETS IF NECESSARY)	SD*45636_11