NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the	L REPORT	118	
WATER RESOURCES DEPARTMENT, STATE OF	OILLOON	/1W-18	
SALEM, OREGON 97310 (Please type within 30 days from the date	or print) ATER RESOURCES DEPT.		
SALEM, OREGON 97310 within 30 days from the date of well completion. (Please type	pove this line) SALEM, CREGUN G-7887	7	
	(10) DOCATION OF WELL:		
(1) OWNER:	1 1/4 - "		
Name Trank Jahnson	County/// Driller's well number	4. C	
Address 8,300/ // Address 1000	14 14 Section 18 T. 63 R.	W.M.	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corn	er	
New Well Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 12.			
	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 22 ft.		
Rotary Driven Domestic Industrial Municipal Domestic Municipal	Static level 45 ft. below land surface.	Date 2-15-7	
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch.	Date	
CASING INSTALLED: Threaded Welded	10		
Threaded Welded Threaded Threa	(12) WELL LOG: Diameter of well below casing		
"Diam. from ft. to ft. Gage	Depth drilled 224 ft. Depth of completed well 222 ft.		
"Diam. from	Formation: Describe color, texture, grain size and structure of materials;		
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation, Report each change in		
PERFORATIONS: Perforated? É Yes No.	position of Static Water Level and indicate principal wa	ater-bearing strata.	
Type of perforator used	MATERIAL From	To SWL	
Size of perforations $3/s$ — in. by 3 in.	Brown Clay 0	20	
252 perforations from 132 ft. to 142 ft.	Brown Soules Clay 20	27	
132 perforations from 150 ft. to 155 ft.	Blue Grey Sandy Clay 27	2.5	
528 perforations from the to 220 it.	Packed Sandond Clay 15	102	
(7) SCREENS: Well screen installed? Yes No.	Suggest 102	104	
7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	Small tothers Groved Sand 104	114	
Manufacturer's Name	Specy Clark 114	117	
Diam. Slot size Set from ft. to ft.	de and a line to the state of the	120	
Diam. Slot size Set from ft. to ft.	mall to Well dianol 120	142	
	May Sande Olar 142	144	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Sorall to Stored because 144	155	
Was a pump test made?	thoug Statel . 155	185	
Id: 535 gal./min. with 56th. drawdown after hrs.	Sould to longer Sports 185	221	
1150 " 177 " 1 "	Sand		
п и н	and the second s		
Bailer test gal./min. with ft. drawdown after hrs.	The set and architecture to the set of the s		
			
	1 21 21	1 / / / / / / / / / / / / / / / / / / /	
perature of water Depth artesian flow encountered ft.	-Work started /- 24 19/6 Completed /-	15- 1976	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1.5 1976	
Well seal-Material used	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
Diameter of well bore to bottom of sealin.	best knowledge and belief.		
Diameter of well bore below seal	[Signed Homen O Terrells Date 1-15 1976		
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator) Drilling Machine Operator's License No. 455.		
How was cement grout placed?	Drilling Machine Operator's License No. 435,		
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief		
Did any strata contain unusable water? Tes PNo	Name / NOSZE NO WELL DRILLING		
	(Person Night Safands) 4510 PALLAS BRINW. DNITTHE TIEM V SALEM, OR 97304		
	Address ONTHING TIENT OF STORY		
Method of sealing strata off	[Signed] Local to Bouilt		
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor)		
Gravel placed fromft_toft.	Contractor's License No. 619 Date 2-16	, 19. 7 :7	