NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED JUN 27 1969 STATE ENGINEER SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 6/1W-18

State Permit No.

3228

MART

(1) OWNER:
Name ARLIN. A. STRAB
Address RT. 2 BOX 224 SILVERTON ORE. 97381

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
8" Diam. from 0 ft. to 180 ft. Gage 1/4"
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used MILLS
Size of perforations 5/16 in. by 2 1/2 in.
430 perforations from 136 ft. to 178 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.
Static level 66'6" ft. below land surface Date 6-18-69
Artesian pressure lbs. per square inch Date

(9) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☐ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 50 gal./min. with 4 ft. drawdown after 1 hrs.
Artesian flow g.p.m. Date
Temperature of water 51° Was a chemical analysis made? ☐ Yes ☒ No

(10) CONSTRUCTION:
Well seal—Material used Bentonite
Depth of seal 50' ft.
Diameter of well bore to bottom of seal 12" in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☒ Yes ☐ No
Did any strata contain unusable water? ☒ Yes ☐ No
Type of water? SANDY depth of strata 101' TO 116
Method of sealing strata off CASED
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:
County MARION Driller's well number
¼ ¼ Section 18 T. 6S R. 1W W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG: Diameter of well below casing 8"
Depth drilled 180 ft. Depth of completed well 180' ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
TOPSOIL	0	3	
CLAY YELLOW COLOR	3	27	
CLAY BLUE SILTY	27	38	
CLAY BLUE STICKY	38	55	
CLAY YELLOW SILTY	55	60	
CLAY BLUE SILTY	60	70	
CLAY YELLOW SANDY	70	72	
CLAY BROWN STICKY	72	101	
CLAY SANDY YELLOW SOFT SAND	101	116	
CONGLOMERATE	116	140	
GRAVEL & SAND 1"	140	141	66'6
CONGLOMERATE WITH INTERMITTENT WATER SEAMS	141	180	66'6

Work started 6-12- 1969 Completed 6-18- 1969
Date well drilling machine moved off of well 6-18- 1969

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] R. F. Sneed (Drilling Machine Operator) Date 6-18, 1969
Drilling Machine Operator's License No. 187

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME S. A. SNEED & SONS (Person, firm or corporation) (Type or print)
Address 3910 SILVERTON RD SALEM ORE.
[Signed] R. F. Sneed (Water Well Contractor)
Contractor's License No. 6 Date 6-18, 1969

(USE ADDITIONAL SHEETS IF NECESSARY)