NOTICE TO WATER WELL CONTRACTOR  The original and first copy of this report  are to be filed with the	LL REPOET EINED				
WATER RESOURCES DEPARTMENT, STATE OF SALEM, OREGON 97310 (Please typ	e or print)				
within 30 days from the date of well completion. (Do not write a	bove WATER RESOURCES DEPTermit NoSALEM_OREGON				
(1) OWNER:	(10) LOCATION OF WELL:				
Name Rueben Ditchen	County Mario Driller's well number				
Address 9712 NUSON RANE	19-15-111				
Silverton Ore 97381					
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner				
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐					
If abandonment, describe material and procedure in Item 12.					
	(11) WATER LEVEL: Completed well.				
Rotary D Driven D	Depth at which water was first found / / ft.				
Cable 🕱 Jetted 🗌 Domestic 🗌 Industrial 🗎 Municipal 🗎	Static level 45 ft. below land surface, Date Ma 417				
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date				
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 12				
John from T tt. to 224 ft. Gage 1250	Doubt dulled 3 20 % But a 12 20				
" Diam. from					
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,				
PERFORATIONS: Perforated? Yes   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.				
Type of perforator used MillS	MATERIAL From To SWL				
Size of perforations in. by in.	topsoil 61'				
336 perforations from $155$ ft. to $169$ ft.	sordy brown clay 1, 36				
perforations from 85 ft. to 19 ft.	blue clay 36 44 60				
45 b perforations from 200 ft. to 219 ft.	brownsandyclay 60: 71				
(7) SCREENS: Well screen installed?   Ves   Ves	black sand Fine 71 95				
(1) SCREENS: Well screen installed?   Yes No Manufacturer's Name	blacksandcoare pagrovel 95" 104				
TypeModel No.	900y c/ay /// 900 \$109 1/3				
Diam. Slot size Set from ft. to ft.	pergrove -cobbels Loss 1/3 /251 55				
Diam. Slot size Set from ft. to ft.	grayclay + grovels small-med 127 1/19				
(0) VICE I INTEGRAL Drawdown is amount water land in	brown clay to sovets small-my 49 152				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Loose gravels med-small 152157 551				
Was a pump test made?   Yes   No If yes, by whom?	coarse brown sand				
gal./min. with /53 ft. drawdown after hrs.	tight gravels small med 157 /63				
" "	osegravels.small-mexcourse 163 169' 55				
n n r r n n	brown sand				
Bailer test gal./min. with ft. drawdown after hrs.	grovels small-med with clay 169 179				
Artesian flow g.p.m.	plagrovel - med course brown 186 191				
erature of water Depth artesian flow encountered ft.					
	Work started Willing machine moved off of well 197				
(9) CONSTRUCTION:  Well seal—Material used Render HE					
Well sealed from land surface to	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.				
m	waterials used and information reported above are true to my				
Diameter of well bore to bottom of seal in.  Diameter of well bore below seal in.	Dest knowledge and benefit.				
Number of sacks of cement used in well seal 2 5015 Devices	[Signed] Date, 19				
How was cement grout placed?	Drilling Machine Operator's License No.				
	and the second s				
	Water Well Contractor's Certification:				
THE RESERVE THE PARTY OF THE PA	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.				
Was a drive shoe used? Xes   No Plugs Size: location ft.	Name FOLA WILL now				
Did any strata contain unusable water?	Name EOLA WELL DRILLING (Type or print)  (Person Sign of Corporation) (Type or print)				
Type of water? depth of strata	Address SALEM, OR BYSHS				
Method of sealing strata off	[Signed] Harry & Board				
Was well gravel packed?   Yes No Size of gravel:	(Water Well Contractor)				
Gravel placed from ft.	Contractor's License No. 619 Date 5-5				
(USE ADDITIONAL SHEETS IF NECESSARY)					

NOTICE TO WATER WELL CONTRACTOR The baiginal and first copy of this report are to be filed with the

are to be filed with the
WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date

## WATER WELL REPORT

## STATE OF OREGON

(Please type or print)

-	7	) 6			
5	Š	aged	<b>-</b>		
S	tate	Well No			
÷ :	tate	Permit No.	********	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	and the state of t

of well completion. (Do not write a	bove this line)
(1) OWNER:	(10) LOCATION OF WELL,
Name Rueben Ditchem	1 h.
Address 97/2 Nusen RD NE	10 15 11)
Silverton Ore 97381	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well   Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
Rotany D Driven D	Depth at which water was first found 179 ft.
Rotary   Driven   Domestic   Industrial   Municipal	Static level 45 ft. below land surface. Date 5-4-7
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Dismeter of well below casing /2"
" Diam. from ft. to ft. Gage	Digitation of Well Beton Cubing
" Diam. from ft. to ft. Gage	Depth drilled 230 ft. Depth of completed well 230 ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated.
PHDEOD A MYONG	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated?	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Continued
perforations from ft. to ft.	<b>※</b> , ,
perforations from ft. to ft.	Claygroy & brown growe 191 193
perforations from ft. to ft.	Coarse brown sand 193 195
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	grovel small-med
The second minutes of the	plagrovel-medigravel 195 2/1
Type Model No	- Choise brown sand
Diam. Slot size Set from ft. to ft.	medglovel-pecglove 211215
Diam. Slot size Set from ft. to ft.	Deachavel - med sand 213219
Eve and a general part of the	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Clay Stone gray 2/9 230
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	- clay stone gray 219 230
gal./min. with ft. drawdown after hrs.	
- "	
" H "	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
erature of water Depth artesian flow encountered ft.	Work started #pc// 1/ 19 77 Completed 5-4 1977
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5-4 19 77
Well seal-Material used	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Date
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
How was cement grout placed?	Drilling Machine Operator's License No. 924
Salina Bir Barren	Water Well Contractor's Certification:
-41-42-32-32-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4-	
7. (1997)	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used?   Yes   No Plugs Size: location ft.	Name EOLA WELL DRILLING
Did any strata contain unusable water?   Yes   No	(Person, firmi∵of coh portaficin) RD, N, W, (Type or print)
Type of water? depth of strata	Address SALEM, OR 97304
Method of sealing strata off	[Signed] of and to Broad
Was well gravel packed?  Yes  No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 619 Date 5-5 , 1975