1965water well report MA

State Well No.

State Permit No.

NOTICE TO WATER WELL CONTRACTOR

The original and first colv of this report are to be flied with the STATE ENGINEER, SALEM, OFFICE ENGINEER, SALEM, OFFICE ENGINEER OF OREGON Within 30 days from the date ALEM OREGON (Please type or print) of well completion.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is		
Name Harold Kloster	lowered below static level Was a pump test made? Yes No If yes, by whom?		
Address Rtx xx Exx Box Rte . 2,	Yield: gal./min. with ft. drawdow		hrs.
Silverton, Oregon	" "		. "
(2) LOCATION OF WELL:	" "		"
County Marion Driller's well number	Bailer test 50 gal./min. with 5 ft. drawdo	wn after	I hrs.
14 14 Section T. R. W.M.	Artesian flow g.p.m. Date	-	
Bearing and distance post section or subdivision corner	Temperature of water Was a chemical analysis r	nade? 🔲	Yes 😿 No
900 ft N, Mosert W, of S.E. cor, of	(12) WELL LOG: Diameter of well below car	sing	3
sec 2I, T6S, RIW, of W.M.	Depth drilled I30 ft. Depth of completed wel		_
	The state of the s		
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each ch	he mater	ial in each
(3) TYPE OF WORK (check):	MATERIAL	FROM	то
New Well	Top soil. brn.	_0_	I
If and donment, describe material and procedure in Item 12.	Clay, grey.	_I_	_25
	Clay, blue grey.	25	39
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Course congl. grey.	39	43
Domestic M Industrial Municipal Rotary Driven	Med congl, grey.	43	49
Irrigation ☐ Test Well ☐ Other ☐ Cable ☐ Jetted ☐ Dug ☐ Bored ☐	Clay, brn.	49	_57
(C) CACING INCHALLED	Sandy clay, with wood, grey	.57	_66
(6) CASING INSTALLED: Threaded Welded	Med congl, med hard, W.B.	66	76
8 "Diam from 0 ft to I25 ft Gage 250	Sandy clay, soft, grey.	7672	78
" Diam. from ft. to ft. Gage	Med congl. med hard. W.B.	78	95
" Diam. fromft. toft. Gage	Med congl. soft, grey. W.B.	95	IÓO
(7) PERFORATIONS: Perforated? N Yes No	Med congl. hard, grey. W.B.	IOO	I25
	Clay, firm, grey.	I25	I30
Type of perforator used Mills			
Size of perforations in. by 3 in 64 perforations from 70 ft. to 75 ft.			
488 perforations from 83 ft. to 124 ft.			
periorations from			
perforations fromft. toft.			
perforations fromft. toft.			
perforations fromft. toft.			
(8) SCREENS: Well screen installed? ☐ Yes IN No			
Manufacturer's Name			
Model No.			·
Slot size Set from ft. to ft.	7.0		<u> </u>
Diam Slot size Set from ft. to ft.		<u>- I9</u>	<u> 19 65</u>
(9) CONSTRUCTION:	Date well drilling machine moved off of well IO- 20		1865
= 1	(13) PUMP:		
Well seal—Material used in seal Bentonite & cuttings	Manufacturer's Name		7
Depth of seal XXX 35 ft. Was a packer used?	Type: H.		
Diameter of well bore to bottom of sealin.		P	
Were any loose strata cemented off? Tyes No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? ▼Yes □ No	This well was drilled under my jurisdiction ar	nd thia .	tonout I-
Was well gravel packed? ☐ Yes X No Size of gravel:	true to the best of my knowledge and belief.	ia tilis i	eport is
Gravel placed fromft. toft.	NAME R. Stadeli & Sons		
Did any strata contain unusable water? Yes 🖪 No	(Person, firm or corporation) (Type	or print)	*
Type of water? depth of strata	Address Rt # 3, Box I69, Silverto	on. O	regm
Method of sealing strata off			m
(10) WATER LEVELS:	Drilling Machine Operator's License No.	[6	***********
·	[Signed] Saul T. Stadeli		
Static level 33 ft. below land surface Date IO-I9-6	(Water Well Contractor)		*********
Artesian pressure lbs. per square inch Date	Contractor's License No. 296 Date II _ I3		10 65
(USE ADDITIONAL SHE	ETS IF NECESSARY)		, 18KJ