

RECEIVED MARI 3292

3292
MARI 3292

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON, within 30 days from the date of well completion.

SEP 23 1963

WATER WELL REPORT

STATE OF OREGON (Please type or print)

State Well No. 6/1W-21R

State Permit No.

(1) OWNER:

Name CLARENCE PREDICT
Address RTE 2, BOX 71
SILVERTON, OREGON

(2) LOCATION OF WELL:

County MARION Driller's well number
S.E. 1/4 S.E. 1/4 Section 21 T. 6 S R. 1 W W.M.
Bearing and distance from section or subdivision corner
1075 ft. West & 75 ft. North from S.E. COR.
of Sec. 21, T. 6 S, R. 1 W. of W.M.

(3) TYPE OF WORK (check):

Well Deepening Reconditioning Abandon
Abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(6) CASING INSTALLED:

Threaded Welded
6" Diam. from 2 ft. to 125'-08" ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(7) PERFORATIONS:

Perforated? Yes No
Type of perforator used MILLS KNIFE
Size of perforations 1/4 in. by 3 in.
335 perforations from 60 ft. to 117 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS:

Well screen installed Yes No
Manufacturer's Name
Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:

Well seal—Material used in seal BENTONITE, GRAVEL + CLAY
Depth of seal 3.2 ft. Was a packer used? YES
Diameter of well bore to bottom of seal 10 in.
Were any loose strata cemented off? Yes No Depth
Was a drive shoe used? Yes No
Was well gravel packed? Yes No Size of gravel: #2 + 3
Gravel placed from 133 ft. to 125 ft. INSIDE
Did any strata contain unusable water? Yes No
Type of water? Depth of strata
Method of sealing strata off

(10) WATER LEVELS:

Static level 14 ft. below land surface Date 7-12-63
Artesian pressure lbs. per square inch Date

(11) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Bailer test 50 gal./min. with 26 ft. drawdown after 1 hr.
Artesian flow g.p.m. Date
Temperature of water ? Was a chemical analysis made? Yes No

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 141 ft. Depth of completed well 125 ft.
Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

MATERIAL	FROM	TO
TOP SOIL - BROWN	0	2
CLAY - BROWN	2	16
" - GREY	16	32
CONGLOMERATE - COURSE - BR.	32	49
CLAY - GREY	49	57
CONGLOMERATE - GREY - MED.	57	119
CLAY - GREYISH GREEN - SOFT + CRUMBLING	119	127
CLAY - GREY - FIRM	127	141
WELL IS FILLED BACK TO 133 WITH SWABBINGS + FROM THERE TO 125' WITH #2 + 3 GRAVEL.		

Work started JUNE 29 1963. Completed JULY 12 1963
Date well drilling machine moved off of well JULY 12 1963

(13) PUMP:

Manufacturer's Name UNIVERSAL
Type: SUBMERSIBLE H.P. 5

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME R. STADEL & SONS
(Person, firm or corporation) (Type or print)

Address RTE 3, BOX 169, SILVERTON, ORE

Drilling Machine Operator's License No. 16

[Signed] Paul R. Stadel
(Water Well Contractor)

Contractor's License No. 296 Date 7-1 1967

