NOTICE TO WATER WELL CONTRACTOR The original and first copy				
of this report are to be WATER WE	LL REPORTEGE VED			
med with the	OREGON State Well No.			
STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.  (Please type) (Po not write a	State Dermit N	. los	s/IW	26dh
of well completion.	bove this the TER RESOURCES DEPT.	O	- J	
	SALEM, CREGON	····		
(1) OWNER:	(10) LOCATION OF WELL:			
Name Jim Souza	County Marion Driller's well number 76-38-6952			
Address 363 Monitor Rd. Silverton, Oregon, 97043	NW 4 SE 4 Section 26 T. 6S R. JW W.M.			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well ★ Deepening  Reconditioning  Abandon	Monitor Rd. off 213			
If abandonment, describe material and procedure in Item 12.				
	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 8 ft.			ft.
Cable	Static level 46 ft. below land surface. Date 7-26-76			
Dug	Artesian pressure lbs. per square inch. Date			
CASING INSTALLED: Threaded Welded	(10)		· · · ·	
6 "Diam. from +1.5 ft. to 27 ft. Gage .250	(12) WELL LOG: Diameter of well below casing			
59/16 " Diam. from +1 ft. to 40 ft. Gage 188	Depth drilled 112 ft. Depth of completed well 100 ft.			
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each stratum	and struc	ture of r	naterials;
DEDECORATIONS	with at least one entry for each change of format	tion. Rep	ort each	chanae in
PERFORATIONS: Perforated?   Yes   No.	position of Static Water Level and indicate prin	cipal wa	ter-bearii	ıg strata.
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.	Top Soil, brwn.	0	2	<u> </u>
perforations from	Clay, lght., brwn., sticky	2	8	
perforations from ft. to ft	Gravel, med., Sandstone, hrd.	8	16	
	Boulders, med., gravel, med	16	21	
(7) SCREENS: Well screen installed? ☐ Yes ☒ No	Sandstone, grey, hrd.	21	39	
Manufacturer's Name	Sandstone, blck.hrd.	39	42	
Type Model No	Rock, basalt, blck., hrd.	42	74	
Diam. Slot size Set from ft. to ft.	Rock, basalt, grey, hrd.	74	92	
Diam. Slot size Set from ft. to ft.	Rock, basalt, blck., soft	92		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Pourous, water	-	108	
Was a pump test made?   Yes No If yes, by whom?	Rock, basalt, blck., hrd.	108	112	
Air Rotary * 68 Total 1 "				
Bailer test gal./min. with ft. drawdown after hrs.	-			
Artesian flow g.p.m.				
Experature of water Depth artesian flow encountered ft.	Work started 7-26- 1976 Complete	d	7-27	<u> 19 7</u> 6
(9) CONSTRUCTION:	Date well drilling machine moved off of well		7-27	<u> 19</u> 76
Well seal—Material used Centent Grout	Drilling Machine Operator's Certification:			
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	direct	super	vision.
Diameter of well bore to bottom of seal in.	best knowledge and belief	above a	are true	to my
Diameter of well bore below seal in.	[Signed] Aller [Mark	Date	7-27	. 19.76
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)			
Number of sacks of bentonite used in well seal Sacks	Drilling Machine Operator's License No81.7			
Brand name of bentonite WiTbur Ellis	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons of water	This well was drilled under my jurisdiction and this report is			
of waterlbs./100 gals.  Was a drive shoe used? ☑ Yes ☐ No Plus Size: location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water!  Yes No	Name S & M Drilling & Sur	bjā.	Inc.	
Type of water? depth of strata	(Person, firm or corporation) (Type or print) Address 399 S.E. Walnut St., Canby, Or., 9701			
Method of sealing strata off	11/2/1500	.A.T.GAA.	~1.1.Y.	
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed] (Water Well Contra	(ctor)	*******************************	
Gravel placed fromft.	Contractor's License No. 497 Date		_ _27	10 76
	Date		<u></u>	., 19