MAR1342 well no. 1 5 1965 THE OF OREGON TE ENGINEER

NO. (Fleese type or print) The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion. STATE ENGINEET OF PRINT ALEM. OREGONE Permit No. ... Drawdown is amount water level is lowered below static level (11) WELL TESTS: John Gerleis 13523 35th Ave. Was a pump test made? Wes I No If yes, by whom? Drillers Name 210 gal./min. with 81 ft. drawdown after / hrx. Seattle Washington (2) LOCATION OF WELL: ft. drawdown after Bailer test gal./min. with hrs. County Marian Driller's well number Artesian flow g.p.m. Date 1/4 Section T. W.M. 🗡 Was a chemical analysis made? 🗌 Yes 🔀 No Temperature of water Bearing and distance from section or subdivision corner (12) WELL LOG: Diameter of well below casing ... 2750 ft. west & 725 ft. south of N.E. corner of section 27, T.6 S. Depth drilled 258 ft. Depth of completed well 257 Formation: Describe by color, character, size of material and structure, and show thickness of aquifiers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. W. of W.M. MATERIAL (3) TYPE OF WORK (check): TOP SOIL - Drown Abandon 🗌 Reconditioning [Deepening [CLay. If abandonment, describe material and procedure in Item 12. Course Conglom. - 9re4 23 30 30 (5) TYPE OF WELL: (4) PROPOSED USE (check): 78 " Conglom-918 Driven 🔲 Domestic | Industrial | Municipal | 87 Jetted [7] Irrigation M Test Well [Other Bored [Softer 90 (6) CASING INSTALLED: 99 med. hard Threaded | Welded 10 "Diam. from 1'-abovett. to 217'-09"#. Gage .279 Packed med Sand grey 10 Bandy Clay-.... ft. to ft. Gage 150 with layers of decayed wood (7) PERFORATIONS: Perforated? A Yes | No Sandy Clay with scattered 197 215 Type of perforator used MILS Perforator med. Gravel 215 217 Size of perforations 3/4 in. by 3 Conglomi-grey-med hard Clay-Soft-Sticky-light grey 217 235 726 perforations from 110 Brian 100-288 femtions everyt 8 on N.E. 235 243 nrow h 245 25 perforations from Side of RhBe. # (8) SCREENS: Well screen installed?

Yes
No Model No. Diam. Slot size Set from ft. to Work started Oct./4 1964. Completed Nev. 30 1964 Diam. Slot size Set from Date well drilling machine moved off of well Nov. 30 1964 (9) CONSTRUCTION: (13) PUMP: Well seal-Material used in seal CLay + Bentonite Manufacturer's Name Diameter of well bore to bottom of seal __________in. Water Well Contractor's Certification: Were any loose strata cemented off? Yes No Depth . Was a drive shoe used? 🔀 Yes 🗌 No This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was well gravel packed? Tyes X No Size of gravel: NAME K. Stade 11 + Son S
(Person, firm or corporation) (Type or print) Gravel placed from ft. g Did any strata contain unusuable water?

Yes No Address-Ric 3 Eaxing Silverton, Oregon Type of water? Method of sealing strata off Drilling Machine Operator's License No. 164322

Contractor's License No. 296 Date 4-9 1965

ft. below and surface Date //_

lbs. per square inch

(10) WATER LEVELS:

Static level 29

Artesian pressure