NOTICE TO WATER WELL CONTRACTOR The original and first copy of this reports

WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT REGELVED

STATE OF OREGON

OCT 14 1981 well No. 65

(Please type or print) WATER RESOURCES DEPT No. not write above this line) SALEM, OREGON (Do not write above this line)

(1) OWNER:	(10) LOCATION OF WELL:		
Name Bob Roth	County Marion Driller's well number		
Address 12513 Hobart Rd. NE	NW 4 SW 4 Section 28 T. 6S R. 1W W.M.		
Silverton, Or 97381	Bearing and distance from section or subdivisi	ion corner	
(2) TYPE OF WORK (check):	-		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	zell	,
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 56	. 011.	££
Domestic Industrial Municipal		surface. Date 1	.0/1/81
Jetted Jetted Irrigation Test Well Other			.0/ 1/ 01
	Artesian pressure lbs. per squar	re inch. Date	
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well 1	helow casing	10"
10 "Diam from +1 ft. to 332 ft. Gage .250	Depth drilled 575 ft. Depth of completed well 575 ft.		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;		
"Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated		
(6) PERFORATIONS: Perforated? ☐ Yes 內 No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used			<u> </u>
	MATERIAL Coll word have	From To	SWL
Size of perforations in. by in.	Soil med brn	0 2	
perforations from	Clay med brn	2 14	
perforations fromft. toft.	Clay med gray Congl. med gray	14 32	
perforations from ft. to ft.	Sand med-fine gray-blk	32 56 56 61	
(7) SCREENS: Well screen_installed? Yes X No	Cravel, clay binder, gry	61 78	
Manufacturer's Name	Conglomerate, large, gry	78 122	
TypeModel No.	Clay med gray	122 178	
Diam Slot size Set from ft. to ft.	Clay med brn	178 252	
Diam. Slot size Set from ft. to ft.	Clay med gray	252 306	
(8) WELL TESTS. Drawdown is amount water level is	Sandstone med green	306 322	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Basalt med blk	322 332	
a pump test made? Yes No If yes, by whom?	Basalt hrd gray	332 541	
gal./min. with ft. drawdown after hrs.	_Claystone hrd green	541 552	
n " " "	Basalt med gray	552 575	WB
Air 500 " drill stem @ 575 "			
er test gal./min. with ft. drawdown after hrs.	-		
A an flow g.p.m.			
Temperature of water Depth artesian flow encounteredft.	W-1- 4 + 10 / 2/1 91	10/1	
Temperature of water Depth around 2011 Character	Work started 9/24 19 81 Completed 10/1 19 81		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	10/1	19 <u>81</u>
Well seal—Material used Cement	Drilling Machine Operator's Certification:		
Well sealed from land surface to 24' & 320-332 ft.	This well was constructed under my	direct supe	rvision.
Diameter of well bore to bottom of seal 14 in.	Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal in.	[Signed] Duran D. Market Date 10/6 1981		
Number of sacks of cement used in well seal 18 sacks	Drilling Machine Operator's License No1371		
How was cement grout placed?	Drining Machine Operator's License No	±	************
	Water Well Contractor's Certification:		
- A	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? Y Yes No Pus Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water Yes X No	Name West Coast Drilling Co, Inc.		
	(Person firm or corporation) Address 220 Academy St. Mt.	(Type or pr	•
Type of water	Address 220 Agademy St. Mt. Angel, Or.		
Method of sealing strata c.f	[Signed] (Mo)(C)	racke (1	,
Was well gravel packed? Yes K No Size of gravel:	(Water Well Contra	,	
Gravel placed from ft. to ft.	Contractor's License No. 519 Date 10	0/6	, 19.81
(USE ADDITIONAL SH	EETS IF NECESSARY)		SD##EGE