NOTICE TO WATER WELL CONTRACTOR The original and first copy

of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED WATER WELL REPORT

STATE OF OREGONAPR 2 8 1975

(Please type or prinSTATE ENGINEER

(Do not write above this SASEM, OREGON

State Well No.	65/1W-2866
----------------	------------

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Zitzelberger Bros.	County Marion Driller's well number
AddressRte.2, Box 151, Silverton, Oregon, 97381	N.W. 14 N.W14 Section 28 T.6 S. R.1 W. W.M.
(9) TYPE OF WORK (short).	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 43 ft.
Rotary Driven Domestic Industrial Municipal	Static level 27 ft. below land surface. Date 3/25/75
Dug Bored Irrigation Test Well Other	Artesian pressure XX lbs. per square inch. Date XX
Threaded Welded Welded 12 Welded 12 Welded 12 Welded 13 Gage 250 Melded 13 Gage 250 Melded 14 Gage 250 Melded 15 Gage 250 Melde	(12) WELL LOG: Diameter of well below casing 0 ft. Depth of completed well 130 ft.
PERFORATIONS: Perforated? XX Yes \(\text{No.} \)	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
PERFORATIONS: Perforated? XXYes \(\square\) No. Type of perforator used Mills Knife	
Size of perforations 7/16 in. by 3 in.	m C 43 3
696 perforations from 50 ft. to 127 ft.	Top Soil-brn.
perforations fromft. toft.	Clay- 22 43
perforations fromft. toft.	Conglom. med.grey- (W.B.) 43 77
perfections from the second se	Gravel- small- grey (W.B.) 77 87
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	Conglom. med. grey- (W.B.) 87 128
Manufacturer's Name	Clay-blue- 128 130
TypeModel No.	120 170
Diam Slot size Set from ft. to ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? In Yes In No If yes, by whom Drillers	
vield: 250 gal./min. with 30 ft. drawdown after 1 hrs.	
325 " 40 " 20-min."	And the second s
" $\frac{1450}{}$ " $\frac{60}{}$ " $2\frac{1}{2}$ hrs."	
YY YY	
perature of waterxx Depth artesian flow encounteredXX ft.	Work started $3/7/75$ 19 Completed $3/25/75$ 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 3/26/75 19
Well seal—Material used Bentonite	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin_	best knowledge and belief.
Diameter of well bore below seal12in.	[Signed] W. A. Date
Number of sacks of cement used in well seal sacks	Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 49/
Brand name of bentonite National	Water Well Contractor's Certification:
Number of pounds of bentonite per $\overline{100}$ gallons	This well was drilled under my jurisdiction and this report is
VI Water 195.7 to gats.	and to the best of my knowledge and belief.
Was a drive shoe used? ┤ Yes ☐ No Plug Size: location ft. Did any strata contain unusable water? ☐ Yes ☒ No	Name B.Stadeli & Sons The
	(Person, firm or corporation) (Type or print)
	Address Rte. 3. Box 169, Silverton, Oregon
Method of sealing strata off	[Signed] Jaul X. Stalli
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor)
Gravel placed from ft.	Contractor's License No. 296 Date 11/1/75 19
(TICH ADDITION	,