NOTICE TO WATER WELL CONTRACTOR The original and first copy	RECEIVED	1		
of this report are to be filed with the	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	15/1		γa
STATE ENGINEED SALEM ODECON 67910		0-11		- 28
within 30 days from the date	pe or print STATE ENGINEER State Permit I	۱۰ ۱۰		
of well completion.	above this ISPLEM. OREGON G68	-		
(1) OWNER:	(10) LOCATION OF WELL:			
Name Robert Roth	County Marion Driller's well number			
Address Rt2, Silverton, Oreg	S.E S.E			
	7192			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATED I EVEL Commission II			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well. Depth at which water was first found 28			
Rotary Driven D				
Cable Defined Domestic Industrial Municipal Dug Bored Inrigation To Test Well Other		surface.	Date 2/	2/ (4
Dug ☐ Bored ☐ Irrigation ☑ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date			
CASING INSTALLED: Threaded Welded N	(12) WELL LOG: Diameter of well		8	**
" Diam. from 0 ft. to 318 ft. Gage 250	Diameter of well below casing			
ft. toft. Gage		,		ft
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	and struc	ture of r	materials;
PERFORATIONS: Perforated? % Ves C No.	with at least one entry for each change of forma	tion. Repo	ort each	change in
Mana Trai Pa	position of Static Water Level and indicate prin	cipal wat	er-beari	ng strata
The state of the s	MATERIAL	From	To	swl
Size of perforations 3/8 in. by 4 in.	Top soil brn.	0	1	
850 perforations from 50 ft. to 116 ft.	Clay brn.	1	12	
perforations from ft. to ft.	Clay grey	12	28	
perforations fromft. toft.	Clay & cbbles grey	28	32	
(7) SCREENS: Well screen installed? ☐ Yes ▼ No	Clay grey	32	38	
Manufacturer's Name	Med Conglomerate greyW.B. Clay sandy blue		112	
Type Model No	Clay blue		130 147	-
Diam. Slot size Set from ft. to ft.	Clay sandy brn.		168	1 3
Diam. Slot size Set from ft. to ft.	Clay sandy grey& wood		172	1
(8) WELL TESTS: Drawdown is amount water level is	Clay sticky blue		184	0
lowered below static level	Cla y blue &few gravels		205	70
Was a pump test made? Yes Do If yes, by whom? Driller	Clay brn & few gravels	205	222	N
Yield: 350 gal./min. with 165 ft. drawdown after $3\frac{1}{2}$ hrs.	Clay grey		262	
" "	Clay brn.		300	V
" " "	J		304	S.
Bailer test gal./min, with ft. drawdown after hrs,			12	ON'
Artesian flow g.p.m. H	. rock brn.		318	<u> </u>
	M. asalt& Streaks of claystone	318 e 360-	$\frac{360}{390}$	\
	Work started 9/26/73 19 2/2/74	d J		19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	2/6/7	4	19
Well seal—Material used Cement	Drilling Machine Operator's Certification:			
Well sealed from land surface to 20 ft.	This well was constructed under my direct supervision.			
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief,			
Diameter of well bore below sealin_	[Signed Fen Taufman 2 Date 2/8/74 , 19			
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	22	,	, 10,
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.			***************************************
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons				
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? May Yes No Plus	Name R. Stadeli& Sons Inc.			
Did any strata contain unusable water? I Yes S No	(Person, firm or corporation) (Type or print) Address Silverton, Oreg			
Type of water? depti of strata	Address			
Method of sealing strata off	[Signed] Taul T. Stadeli			
Was well gravel packed? ☐ Yes X No Size of gravel:	(Water Well Contractor)			
Gravel placed from ft ft.	Contractor's License No. 296 Date2/	8 /74		, 19
(USE ADDITIONAL SH	EETS IF NECESSARY)			*45656-119