NOTICE TO WATER WELL CONTRACTOR
The original and first copy

of this report are to be

filed with the

RECEIVED WATER WELL REPORT

DEC5 1974_{State Well No.} 65/1W-28 CC

SP*45656-119

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

STATE OF OREGON

(Please type or print) STATE ENGINEER
(Do not write above this line SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:			
Name Larry Mathews	County Marion Driller's well number			
Address Rt2 Silverton, Or.	S.W. 14S.W. 14 Section 28 T6.S.	R1.W.		W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corne	r	
New Well 4 Deepening Reconditioning Abandon	<u> </u>			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	zell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 39			
Rotary Driven Domestic M Industrial Municipal	Static level 42 ft. below land s		Data 10	/21 /7/1
Cable				
A state of the sta	Artesian pressure lbs. per squar	e inch.	Date	
CASING INSTALLED: Threaded Welded M	(12) WELL LOG: Diameter of well to		6	
6 "Diam. from ft. to 94 ft. Gage •250	100			
" Diam. from ft. to ft. Gage	I Depth drilled LVM - ft Depth of completed well Vth - st			
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size	and struc	ture of r	naterials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in			
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal wat	er-bearin	ng strata.
Type of perforator used	MATERIAL	From	то	SWL
Size of perforations in. by in.	Top soil brn.	0	1	
perforations from	Clay brn.	1	22	
perforations from ft. to ft.	Clay grey.	22	38	
-	Med Conglomerate grey	38	61	
perforations from ft. to ft.	ununununununun brn.	61	83	
(7) SCREENS: Well screen installed? Yes X No	manusummunumm grey	83	-	
Manufacturer's Name	Looser sand& gravel grey W.B.	94	94 109	
Type Model No.	-coser banka graver grey m.b.	74	109	
Diam. Slot size Set from ft. to ft.				
Diam Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is				
lowered below static level				
Was a pump test made? Yes No If yes, by whom?				
Wield: gal./min. with ft. drawdown after hrs.				
" " "				
" <u>*</u> " "				
Rail'r test 80 gal./min. with 52 ft. drawdown after 1 hrs.				
i i i i i i i i i i i i i i i i i i i				
	10/20/20	40/04	/m.l.	
perature of water Depth artesian flow encountered ft.		$\frac{10}{31}$		_19
(9) CONSTRUCTION:	Date well drilling machine moyed off of well.	/31/74	<u>. </u>	19
Well seal—Material used Bentonite	Drilling Machine Operator's Certification:			
Well sealed from land surface toft.	This well was constructed under my	direct	super	vision.
Diameter of well bore to bottom of real 10 in.	Materials used and information reported best knowledge and belief.	above a	re true	to my
Diameter of well bore below seal in.		Date 11/	6/71	10
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	960		,
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No		~	
Brand name of bentonite Quick gell		<u> </u>		
Number of pounds of bentonite per 100 gallins	Water Well Contractor's Certification:			
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is			
Was a drive shoe used? I Yes I No Plus Size: location ft.	true to the best of my knowledge and believed R. Stadelie Sons Inc.	eī.		
Did any strata contain unusable water? Tyes 🖪 No	(Person, firm or corporation)	(Tran	e or prin	
Type of water? depth of strata	Address Silverton.Oreg.	(23)	- or bill	*/
Method of sealing strata off	(2:10 (D) 8+ 0.1.			
Was well gravel packed? ☐ Yes Y No Size of gravel:	[Signed] Water Well Contractor)			
Gravel placed fromft.			29	3
(USE ADDITIONAL SH	Date ././ Date ././	- 9 - 1	<i></i>	, 19
E COM ADDITIONAL SH	LLIB IF NECESSARY)		STE	45658_110