NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report

are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

r 3!	"State Well No. 45/1W - 8 bq
RI.	State Well No. / S/100 - 8 bq
WELL	State Permit No.
•	State/Tellifit No

4 - 22					
(1) OWNER:	(10) LOCATION OF WELL:				
Name AKATY KONEY	County MARION Driller's well no	umber			
Address 875 BROWN RD	SE 14 NN 14 Section 8 T. 45	R. / 1/L	T	W.M.	
WOOD BURN, DE	Bearing and distance from section or subdivisi				
(2) TYPE OF WORK (check):	Bearing and distance from Section of Subdiving	ion corner			
New Well ☑ Deepening □ Reconditioning □ Abandon □					
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL Completed on				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.				
Rotary Driven Domestic Manicipal Domestic Manicipal Domestic Manicipal Domestic Description	Depth at which water was first found 2/ ft.				
Cable Jetted I	Static level 60 ft. below land surface. Date 6/30/79 Artesian pressure lbs. per square inch. Date				
CASING INSTALLED: Threaded □ Welded B 8 "Diam. from 0 ft. to 1.72 ft. Gage250 "Diam. from ft. to ft. Gage	(12) WELL LOG: Diameter of well below casing Depth drilled /72 ft. Depth of completed well /72 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,				
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.				
Type of perforator used STAR	MATERIAL	From	То	swL	
Size of perforations / 1/2 in. by 3/8 in.	TOPSOIL	c ³	3		
225 perforations from 150 ft. to 165 ft.	CLAY BROWN	3 .	21		
perforations from ft. to ft.	SILT BROWN	21 0	23	12	
perforations from ft. to ft.	CLAY BLUE	3 3	52		
(7) SCREENS: Well screen installed? The No.	CLAY BROWN	1 1	63		
	SILT BROWN		72		
Manufacturer's Name	SAND BROWN		84	22_	
Diam. Slot size Set from ft. to ft.	Sicr Brown	1 . 	89		
Diam. Slot size Set from ft. to ft.	SANSTONE BEOWN	 	72	22	
200 320 320 320 320 320 320 320 320 320	CEMENT Graver Grey		17.5		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Carry Deux		130		
Was a pump test made? ☑ Yes ☐ No If yes, by whom?	CIAN COM		172	60	
183	-CITY GFEY	100			
	- 4				
	*****	1 1 1			
И И И					
Bailer test gal./min. with ft. drawdown after hrs.					
Artesian flow g.p.m.					
perature of water 51 Depth artesian flow encountered ft.	Work started 6 / 26/ 1975 Complete	ed 6/3.	'o/	1979	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	G / 30		19 79	
Well seal-Material used Cement Drilling Machine Operator's Certification:					
Well sealed from land surface to $\mathcal{A}\delta$ ft.	This well was constructed under my Materials used and information reported				
Diameter of well bore to bottom of seal in.	best knowledge and belief		_		
Diameter of well bore below seal	[Signed] Tuker Back	Date 4/	321	19.25	
Number of sacks of cement used in well seal sacks	(Drilling Magnine Operator)				
How was cement grout placed? Humped	Drilling Machine Operator's License No.	.7.20		•	
	Water Well Contractor's Certification:				
	This well was drilled under my jurisd	iction and	this re	port is	
Was a drive shoe used? ✓ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.				
Did any strata contain unusable water? Yes P No	Name (Person, firm or corporation)	[ell(f):	/////	12 g	
Type of water? depth of strata	Address 21/637 9 8 Ky/22	_ D, C	226	yore	
Method of sealing strata off	(/)	1)	<u></u>	゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚゚	
	[Signed] John Wolf Sont	ere.			
Was well gravel packed? Yes No Size of gravel:	(Water Well Contr		n	د و	
Gravel placed from ft. to ft.	Contractor's License No Date	6-30		, 19 <i>C</i> ?	