NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the				
WATE RESOURCES DEPARTMENT STATE OF	1761. 71977		11W -	CC
SALEM, OREGON 97310 within 30 days from the date of well completion. (Do not write above the OREGON CALEM OREGON				
of well completion. (Do not write a	ATER RESOURCES DE	V by	GCS	***************************************
	SALL	- 0		
OWNER: e Chester Tucker	(10) LOCATION OF WELL:			
0.0	County //opton Driller's well number			
Truner present	34 14 Section 33 T. 65 R. / W W.M.			
2) TYPE OF WORK (check):	Bearing and distance from section or subdivis	ion corn	er	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WARRED LEWISH Committee 1			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.			
tary Pl Driven D	Depth at which water was first found 64 ft.			
e ,	Static level ft. below land	w land surface. Date //-/5-7		
Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date			
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 8			
1 Diam. from 1 ft. to 125 ft. Gage 150	of well select cashing			
" Diam, from ft. to ft. Gage				
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,			
(6) PERFORATIONS: Perforated? Yes Pro.	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Rer	port each	change in
Type of perforator used	MATERIAL	T	1	
Size of perforations in. by in.	Brown Clay	From	To	SWL
perforations fromft. toft.	mount day	1	23	
perforations from ft. to ft.	Due Clare	25	3.5	
perforations fromft. toft.		1000	<u>.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</u>	
	Comented Grovel	35	66	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No				
Manufacturer's Name	Amall Granel	106	73	
Type Model No.	AA A			
Diam. Slot size Set from ft. to ft.	Blue clay	2.3	70	
Je se	- land	912	03	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Jano,	10	9.3	
pump test made? Yes No If yes, by whom?	Brown Clay Blue Stan	193	120	
Yi. d: gal./min. with ft. drawdown after hrs.			, , ,	
" " " "	Granels	120	123	
h, ra " " " "				
test 60 gal./min. with 15 ft. drawdown after hrs.	May Clayolone	125	140	
A clan flow g.p.m.				VII
Temperature of water Depth artesian flow encountered ft.	Week started 11-10 to 76		10	46
	Work started //-/ 19 / Complete	:d //	-/2	1979
(9) CONSTRUCTION:	Date well drilling machine moved off of well	_//	-/5	19 79
Well seal—Material used Coment	Drilling Machine Operator's Certification:			
Wassealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my			
Diameter of well bore to bottom of seal in.	best knowledge and belief.			
Diameter of well bore below seal	(Drilling Machine Operator)			
Number of sacks of cement used in well seal sacks How was cement grout placed?	Drilling Machine Operator's License No. 455			
Remped				
The state of the s	Water Well Contractor's Certification:			
	This well was drilled under my jurisdiction and this report is			
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and beliefEOLA WELL DRILLING Name 4510 DALLAS RD NW			
Did any strata contain unusable water? Yes No	Name 4510 DALLAS RD, N.W. (Person, firm or corporation) SALEM, OF \$73.04			
Type of water? depth of strata	Address		*****************	- /
Method of sealing strata off	[Signed] Acrest IV Rendt			
/as well gravel packed? ☐ Yes ☐ No size of gravel:(Water Well Contractor)				
Gravel placed from ft. to ft.	Contractor's License No. 19 Date //	1-28	2	., 1977
(USE ADDITIONAL SW	PERO TE MOCIOCA DEL			