

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No. 65/1W-34ba

State Permit No. 65/1-34ba

(1) OWNER:

Name Vic David

Address Silverton, Oregon

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☒

6 " Diam. from +2 ft. to 88 ft. Gage 250

" Diam. from " ft. to " ft. Gage "

" Diam. from " ft. to " ft. Gage "

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No

Type of perforator used

Size of perforations in. by in.

perforations from " ft. to " ft.

perforations from " ft. to " ft.

perforations from " ft. to " ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from " ft. to " ft.

Diam. Slot size Set from " ft. to " ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: 18 gal./min. with 32 ft. drawdown after 7 hrs.

" " " "

" " " "

Bailer test 18 gal./min. with 32 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered " ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite + Foddlclay

Well sealed from land surface to 22 ft.

Diameter of well bore to bottom of seal 10 in.

Diameter of well bore below seal 6 in.

Number of sacks of cement used in well seal sacks

Number of sacks of bentonite used in well seal sacks

Brand name of bentonite National

Number of pounds of bentonite per 100 gallons

of water 50 lbs./100 gals.

Was a drive shoe used? ☒ Yes ☐ No Phy Size: location " ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel: " to " ft.

Gravel placed from " to " ft.

(10) LOCATION OF WELL:

County Marion Driller's well number

NE 1/4 NW 1/4 Section 34 T. 6 R. 1 W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 60 ft.

Static level 36 ft. below land surface. Date 6/14/72

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6 "

Depth drilled 113 ft. Depth of completed well 94 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	5	
Clay	5	24	
Boulders & gravel	24	38	
shale	38	44	##
Brown clay boulders gravel	44	68	44
Blocky clay-gravel	68	94	
sand and clay	94	99	36
gravel & sand	99	113	76
Pulled back			
casing to 88 ft.			

Work started 6/6 1972 Completed 6/14 1972

Date well drilling machine moved off of well 6/14 1972

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] A. C. Burns Date 6/14, 1972
(Drilling Machine Operator)

Drilling Machine Operator's License No. 766

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Duffield Bros
(Person, firm or corporation) (Type or print)

Address 4123 Bluff Ave SE, Salem, Ore

[Signed] Howard Duffield
(Water Well Contractor)

Contractor's License No. 15 Date 6/15, 1972

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119